



flow90CON 1

1600 V / 36 A

Topology features

- Three-phase Half Controlled Converter

Component features

- High inrush current capability

Housing features

- Base isolation: Al_2O_3
- 90° mounting angle between heatsink and PCB
- Screw-on heatsink mounting
- Clip-in PCB mounting
- Thermo-mechanical push-and-pull force relief
- Solder pin


Target applications

- Motor drives
- Servo drives


Types

- V23990-P717-H10-PM

flow90 1 housing



Schematic





Vincotech

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Rectifier Thyristor				
Repetitive peak reverse voltage	V_{RRM}		1200	V
Maximum RMS on-state current	I_{TRMSM}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	45	A
Surge on-state current	I_{TSM}	Single Half Sine Wave, $t_p = 10\text{ ms}$ $T_j = 150\text{ °C}$	360	A
I2t value	I^2t	Single Half Sine Wave, $t_p = 10\text{ ms}$ $T_j = 150\text{ °C}$	650	A ² s
Mean total power loss	$P_{tot}(AV)$	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	68	W
Maximum Junction Temperature	T_{jmax}		150	°C

Rectifier Diode

Peak repetitive reverse voltage	V_{RRM}		1600	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	63	A
Surge (non-repetitive) forward current	I_{FSM}	Single Half Sine Wave, $t_p = 10\text{ ms}$ $T_j = 150\text{ °C}$	520	A
Surge current capability	I^2t		1350	A ² s
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	73	W
Maximum junction temperature	T_{jmax}		150	°C

Module Properties

Thermal Properties

Storage temperature	T_{stg}		-40...+125	°C
Operation temperature under switching condition	T_{jop}		-40...+($T_{jmax} - 25$)	°C

Isolation Properties

Isolation voltage	V_{isol}	DC Test Voltage* $t_p = 2\text{ s}$	6000	V
Creepage distance			>12,7	mm
Clearance			11,84	mm
Comparative Tracking Index	CTI		≥ 200	

*100 % tested in production



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Rectifier Thyristor

Static

On-state voltage	V_T				45	25 125		1,54 1,66	1,4 1,45	V
Direct reverse current	I_{RD}	$V_r = 1200$ V				25 150			50 8000	μA
Holding current	I_H	$I_T = A$		6		25		100		mA
Latching current	I_L	$t_p = 10$ μs $I_G = 0,3$ A $di_G/dt = 0,3$ A/μs				25		150		mA
Gate trigger voltage	V_{GT}			6		25			1,5	V
Gate trigger current	I_{GT}			6		25			55	mA
Gate non-trigger current	I_{GD}					25			3000	nA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)						1,02		K/W
--	---------------	------------------------------------	--	--	--	--	--	------	--	-----

Rectifier Diode

Static

Forward voltage	V_F				80	25 125 150		1,27 1,27	1,33 ⁽¹⁾ 1,31 ⁽¹⁾	V
Reverse leakage current	I_R	$V_r = 1600$ V				25 150			20 1500	μA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)						0,96		K/W
--	---------------	------------------------------------	--	--	--	--	--	------	--	-----

⁽¹⁾ Value at chip level

⁽²⁾ Only valid with pre-applied Vincotech thermal interface material.



Vincotech

V23990-P717-H10-PM
datasheet

Rectifier Thyristor Characteristics

figure 1. Thyristor

Typical forward characteristics

$$I_F = f(V_F)$$





figure 2. Thyristor

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



Thyristor thermal model values

R (K/W)	τ (s)
1,01E-01	1,45E+00
2,12E-01	2,65E-01
4,76E-01	7,87E-02
1,89E-01	1,28E-02
4,45E-02	1,54E-03



Rectifier Diode Characteristics

figure 3.

Rectifier

Typical forward characteristics

$$I_F = f(V_F)$$





figure 4.

Rectifier

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D =$	t_p / T	
$R_{th(j-s)} =$	0,965	K/W
Rectifier thermal model values		
R (K/W)	τ (s)	
3,98E-02	7,88E+00	
1,29E-01	8,64E-01	
4,20E-01	1,32E-01	
2,76E-01	4,24E-02	
6,63E-02	5,80E-03	
3,37E-02	8,90E-04	




Vincotech

V23990-P717-H10-PM

datasheet

Ordering Code	
Version	Ordering Code
Without thermal paste	V23990-P717-H10-PM
With thermal paste (3,4 W/mK, PSX-P7)	V23990-P717-H10-/3/-PM


Marking							
	Text	VIN	Date code	Type&Ver	UL	Lot	Serial
		VIN	WWYY	TTTTTTTV	UL	LLLL	SSSS
	Datamatrix	Type&Ver	Lot number	Serial	Date code		
		TTTTTTTV	LLLL	SSSS	WWYY		

Outline			
Pin table [mm]			
Pin	X	Y	Function
1	53	0	L3
2	50,1	0	L3
3	47,2	0	L3
4	40,2	0	L1
5	37,3	0	L1
6	34,4	0	L1
7	27,4	0	G3
8	24,5	0	G2
9	21,6	0	G1
10	18,7	0	DC+
11	15,8	0	DC+
12	12,9	0	DC+
13	7,1	0	NA
14	0	0	NA
15	0	7	NA
16	3	7	NA
17	7	7	DC-
18	9,9	7	DC-
19	12,8	7	DC-
20	44	7	L2
21	47	7	L2
22	50	7	L2

Tolerance of positions: ±0,5mm at the end of pins
Dimension of coordinate axis is only offset without tolerance



Pinout



Identification

ID	Component	Voltage	Current	Function	Comment
T1, T2, T3	Thyristor	1200 V	45 A	Rectifier Thyristor	
D1, D2, D3	Rectifier	1600 V	42 A	Rectifier Diode	



Packaging instruction				
Standard packaging quantity (SPQ) 80	>SPQ	Standard	<SPQ	Sample

Handling instruction
Handling instructions for <i>flow90</i> 1 packages see vincotech.com website.

Package data
Package data for <i>flow90</i> 1 packages see vincotech.com website.

Vincotech thermistor reference
See Vincotech thermistor reference table at vincotech.com website.

UL recognition and file number
This device is certified according to UL 1557 standard, UL file number E192116. For more information see vincotech.com website.



Document No.:	Date:	Modification:	Pages
V23990-P717-H10-PM-D5-14	25 Sep. 2022	New Datasheet format, module is unchanged Introduce Rth values with PSX-P7	

DISCLAIMER

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.