



Vincotech

10-F012NME080SH-M910F09

datasheet

flowMNPC 0

1200 V / 80 A

Features

- Mixed voltage component topology
- Neutral point clamped inverter
- Pin compatibility to P96x NPC family
- LVRT and reactive power capability


Target applications

- Solar inverter
- UPS


Types

- 10-F012NME080SH-M910F09

flow 0 17 mm housing



Schematic





Vincotech

10-F012NME080SH-M910F09
datasheet

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Buck Switch				
Collector-emitter voltage	V_{CES}		1200	V
Collector current (DC current)	I_C	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	76	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	240	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	186	W
Gate-emitter voltage	V_{GES}		± 20	V
Short circuit ratings	t_{SC}	$V_{GE} = 15\text{ V}$, $V_{CC} = 800\text{ V}$ $T_j = 150\text{ °C}$	10	μs
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$

Buck Diode

Peak repetitive reverse voltage	V_{RRM}		600	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	51	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	69	W
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$

Boost Switch

Collector-emitter voltage	V_{CES}		600	V
Collector current (DC current)	I_C	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	65	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	225	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	101	W
Gate-emitter voltage	V_{GES}		± 20	V
Short circuit ratings	t_{SC}	$V_{GE} = 15\text{ V}$, $V_{CC} = 360\text{ V}$ $T_j = 150\text{ °C}$	6	μs
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$



Vincotech

10-F012NME080SH-M910F09
datasheet

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Boost Diode				
Peak repetitive reverse voltage	V_{RRM}		1200	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	31	A
Surge (non-repetitive) forward current	I_{FSM}	Single Half Sine Wave, $t_p = 10\text{ ms}$ $T_j = 150\text{ °C}$	170	A
Surge current capability	I^2t		145	A ² s
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	71	W
Maximum junction temperature	T_{jmax}		175	°C

Module Properties

Thermal Properties

Storage temperature	T_{stg}		-40...+125	°C
Operation temperature under switching condition	T_{jop}		-40...+($T_{jmax} - 25$)	°C

Isolation Properties

Isolation voltage	V_{isol}	DC Test Voltage* $t_p = 2\text{ s}$	6000	V
Isolation voltage	V_{isol}	AC Voltage $t_p = 1\text{ min}$	2500	V
Creepage distance			>12,7	mm
Clearance			>12,7	mm
Comparative Tracking Index	CTI		≥ 200	

*100 % tested in production



Vincotech

10-F012NME080SH-M910F09
datasheet

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Buck Switch

Static

Gate-emitter threshold voltage	$V_{GE(th)}$	$V_{CE} = V_{GE}$			0,003	25	5,3	5,8	6,3	V
Collector-emitter saturation voltage	$V_{CE(sat)}$		15		80	25 125 150	1,78	1,99 2,33 2,41	2,42 ⁽¹⁾	V
Collector-emitter cut-off current	I_{CES}		0	1200		25			10	µA
Gate-emitter leakage current	I_{GES}		20	0		25			240	nA
Internal gate resistance	r_g							None		Ω
Input capacitance	C_{ies}	$f = 1 \text{ Mhz}$	0	25		25		4660		pF
Output capacitance	C_{oes}							300		pF
Reverse transfer capacitance	C_{res}							260		pF
Gate charge	Q_g	$V_{CC} = 960 \text{ V}$	15		80	25		370		nC

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4 \text{ W/mK}$ (PSX)						0,51		K/W
--	---------------	---	--	--	--	--	--	------	--	-----

Dynamic

Turn-on delay time	$t_{d(on)}$	$R_{gon} = 4 \Omega$ $R_{goff} = 4 \Omega$	± 15	350	56	25 125		77,6 78,8		ns
Rise time	t_r					25 125		13 15,4		ns
Turn-off delay time	$t_{d(off)}$					25 125		170,4 220,8		ns
Fall time	t_f					25 125		43,2 68,24		ns
Turn-on energy (per pulse)	E_{on}	$Q_{iFWD}=1,01 \mu C$ $Q_{iFWD}=2,74 \mu C$				25 125		0,473 0,972		mWs
Turn-off energy (per pulse)	E_{off}					25 125		1,28 2,17		mWs



Vincotech

10-F012NME080SH-M910F09
datasheet

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Buck Diode

Static

Forward voltage	V_F				60	25 125 150		2,27 1,68 1,58	2,8 ⁽¹⁾	V
Reverse leakage current	I_R	$V_i = 600$ V				25			10	µA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)						1,38		K/W
--	---------------	---------------------------------------	--	--	--	--	--	------	--	-----

Dynamic

Peak recovery current	I_{RRM}	$di/dt=4710$ A/µs $di/dt=4651$ A/µs	± 15	350	56	25 125		64,27 83,05		A
Reverse recovery time	t_{rr}					25 125		28,7 73,13		ns
Recovered charge	Q_r					25 125		1,01 2,74		µC
Reverse recovered energy	E_{rec}					25 125		0,172 0,521		mWs
Peak rate of fall of recovery current	$(di_{rr}/dt)_{max}$					25 125		9597 3522		A/µs



Vincotech

10-F012NME080SH-M910F09
datasheet

Characteristic Values

Parameter	Symbol	Conditions						Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max		

Boost Switch

Static

Gate-emitter threshold voltage	$V_{GE(th)}$	$V_{CE} = V_{GE}$			0,0012	25	5	5,8	6,5	V
Collector-emitter saturation voltage	$V_{CE(sat)}$		15		75	25 125 150	1,05	1,45 1,59 1,64	1,85 ⁽¹⁾	V
Collector-emitter cut-off current	I_{CES}		0	600		25			3,8	µA
Gate-emitter leakage current	I_{GES}		20	0		25			600	nA
Internal gate resistance	r_g							None		Ω
Input capacitance	C_{ies}	$f = 1 \text{ Mhz}$	0	25		25		4620		pF
Output capacitance	C_{oes}							288		pF
Reverse transfer capacitance	C_{res}							137		pF
Gate charge	Q_g	$V_{CC} = 480 \text{ V}$	15		75	25		470		nC

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4 \text{ W/mK}$ (PSX)						0,94		K/W
--	---------------	---	--	--	--	--	--	------	--	-----

Dynamic

Turn-on delay time	$t_{d(on)}$	$R_{gon} = 4 \text{ } \Omega$ $R_{goff} = 4 \text{ } \Omega$	± 15	350	56	25 125 150		86 87 86,6		ns
Rise time	t_r					25 125 150		12,2 13,2 13,4		ns
Turn-off delay time	$t_{d(off)}$					25 125 150		172,8 200,2 206,4		ns
Fall time	t_f					25 125 150		72,92 95,63 96		ns
Turn-on energy (per pulse)	E_{on}					25 125 150		0,435 0,681 0,75		mWs
Turn-off energy (per pulse)	E_{off}					25 125 150		1,75 2,34 2,46		mWs



Vincotech

10-F012NME080SH-M910F09
datasheet

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Boost Diode

Static

Forward voltage	V_F				35	25 125 150		2,28 2,41 2,37	2,62 ⁽¹⁾ 2,62 ⁽¹⁾	V
Reverse leakage current	I_R	$V_i = 1200$ V				25 150		2700	60 5500	µA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)						1,34		K/W
--	---------------	---------------------------------------	--	--	--	--	--	------	--	-----

Dynamic

Peak recovery current	I_{RRM}	$di/dt=5389$ A/µs $di/dt=3855$ A/µs $di/dt=3963$ A/µs	± 15	350	56	25 125 150		85,75 97,34 104,63		A
Reverse recovery time	t_{rr}					25 125 150		32,33 89,76 99,07		ns
Recovered charge	Q_r					25 125 150		2,96 5,5 6,87		µC
Reverse recovered energy	E_{rec}					25 125 150		0,804 1,55 1,96		mWs
Peak rate of fall of recovery current	$(di_{rr}/dt)_{max}$					25 125 150		6668 5971 5963		A/µs



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Thermistor

Static

Rated resistance	R					25		22		kΩ
Deviation of R_{100}	$\Delta_{R/R}$	$R_{100} = 1484 \Omega$				100	-5		5	%
Power dissipation	P							5		mW
Power dissipation constant	d					25		1,5		mW/K
B-value	$B_{(25/50)}$	Tol. $\pm 1 \%$						3962		K
B-value	$B_{(25/100)}$	Tol. $\pm 1 \%$						4000		K
Vincotech Thermistor Reference									I	

⁽¹⁾ Value at chip level

⁽²⁾ Only valid with pre-applied Vincotech thermal interface material.



Vincotech

10-F012NME080SH-M910F09


datasheet

Buck Switch Characteristics

figure 1. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $V_{GE} = 15 V$
 $T_j:$ 25 °C, 125 °C, 150 °C

figure 2. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $T_j = 150 \text{ } ^\circ\text{C}$
 V_{GE} from 7 V to 17 V in steps of 1 V

figure 3. IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$




$t_p = 250 \mu s$
 $V_{CE} = 10 V$
 $T_j:$ 25 °C, 125 °C, 150 °C

figure 4. IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 0.512 \text{ K/W}$
IGBT thermal model values

$R \text{ (K/W)}$	$\tau \text{ (s)}$
9.50E-02	1.05E+00
1.84E-01	1.66E-01
1.81E-01	6.37E-02
3.37E-02	7.18E-03
1.79E-02	6.47E-04



Vincotech


10-F012NME080SH-M910F09
datasheet

Buck Switch Characteristics

figure 5. IGBT

Safe operating area

$$I_C = f(V_{CE})$$



D = single pulse

$T_s = 80$ °C

$V_{GE} = 15$ V

$T_j = T_{jmax}$



Vincotech

Buck Diode Characteristics

figure 6.

FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 7.

FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D =$	t_p / T	
$R_{th(j-s)} =$	1,379	K/W
FWD thermal model values		
R (K/W)	τ (s)	
8,16E-02	3,99E+00	
2,02E-01	6,32E-01	
7,09E-01	1,11E-01	
2,16E-01	3,68E-02	
9,74E-02	5,31E-03	
7,28E-02	1,31E-03	



Vincotech

10-F012NME080SH-M910F09


datasheet

Boost Switch Characteristics

figure 8. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $V_{GE} = 15 V$
 $T_j:$ 25 °C, 125 °C, 150 °C

figure 9. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $T_j = 150 \text{ } ^\circ C$
 V_{GE} from 7 V to 17 V in steps of 1 V

figure 10. IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$




$t_p = 250 \mu s$
 $V_{CE} = 10 V$
 $T_j:$ 25 °C, 125 °C, 150 °C

figure 11. IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 0,94 \text{ K/W}$
IGBT thermal model values

$R \text{ (K/W)}$	$\tau \text{ (s)}$
8,42E-02	4,56E+00
2,89E-01	4,19E-01
4,35E-01	7,20E-02
8,50E-02	2,19E-02
4,67E-02	1,33E-03



Vincotech

10-F012NME080SH-M910F09
datasheet


Boost Switch Characteristics

figure 12.

IGBT

Safe operating area

$I_C = f(V_{CE})$



$D =$ single pulse

$T_s = 80$ °C

$V_{GE} = 15$ V

$T_j = T_{jmax}$



Vincotech


Boost Diode Characteristics

figure 13.

FWD

Typical forward characteristics

$$I_F = f(V_F)$$



$t_p = 250 \mu s$

T_j :


- 25 °C
- 125 °C
- 150 °C

figure 14.

FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$

$R_{th(j-s)} = 1,342 \text{ K/W}$

FWD thermal model values

$R \text{ (K/W)}$	$\tau \text{ (s)}$
$3,06E-02$	$9,16E+00$
$1,47E-01$	$6,10E-01$
$6,10E-01$	$8,89E-02$
$2,96E-01$	$2,14E-02$
$1,39E-01$	$5,05E-03$
$1,19E-01$	$9,19E-04$



Vincotech

10-F012NME080SH-M910F09
datasheet


Thermistor Characteristics

figure 15.

Thermistor

Typical NTC characteristic as function of temperature

$$R_T = f(T)$$





Vincotech

10-F012NME080SH-M910F09
datasheet


Buck Switching Characteristics

figure 16.

IGBT

Typical switching energy losses as a function of collector current

$$E = f(I_C)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 4$ Ω
 $R_{goff} = 4$ Ω


T_j : — 25 °C
— 125 °C

figure 17.

IGBT

Typical switching energy losses as a function of gate resistor

$$E = f(R_g)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $I_C = 56$ A


T_j : — 25 °C
— 125 °C

figure 18.

FWD

Typical reverse recovered energy loss as a function of collector current

$$E_{rec} = f(I_C)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 4$ Ω


T_j : — 25 °C
— 125 °C

figure 19.

FWD

Typical reverse recovered energy loss as a function of gate resistor

$$E_{rec} = f(R_g)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $I_C = 56$ A

T_j : — 25 °C
— 125 °C



Vincotech

10-F012NME080SH-M910F09
datasheet


Buck Switching Characteristics

figure 20.

IGBT

Typical switching times as a function of collector current

$$t = f(I_C)$$



With an inductive load at


$T_j =$	125	$^{\circ}C$
$V_{CE} =$	350	V
$V_{GE} =$	± 15	V
$R_{gon} =$	4	Ω
$R_{goff} =$	4	Ω

figure 21.

IGBT

Typical switching times as a function of gate resistor

$$t = f(R_g)$$



With an inductive load at


$T_j =$	125	$^{\circ}C$
$V_{CE} =$	350	V
$V_{GE} =$	± 15	V
$I_C =$	56	A

figure 22.

FWD

Typical reverse recovery time as a function of collector current

$$t_{rr} = f(I_C)$$



With an inductive load at

$V_{CE} =$	350	V
$V_{GE} =$	± 15	V
$R_{gon} =$	4	Ω


T_j :
— 25 $^{\circ}C$
— 125 $^{\circ}C$

figure 23.

FWD

Typical reverse recovery time as a function of IGBT turn off gate resistor

$$t_{rr} = f(R_{goff})$$



With an inductive load at

$V_{CE} =$	350	V
$V_{GE} =$	± 15	V
$I_C =$	56	A

T_j :
— 25 $^{\circ}C$
— 125 $^{\circ}C$



Vincotech

10-F012NME080SH-M910F09
datasheet


Buck Switching Characteristics

figure 24.

FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 4$ Ω


T_j : — 25 °C
— 125 °C

figure 26.

FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 4$ Ω


T_j : — 25 °C
— 125 °C

figure 25.

FWD

Typical recovered charge as a function of turn off gate resistor

$$Q_r = f(R_{goff})$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $I_c = 56$ A


T_j : — 25 °C
— 125 °C

figure 27.

FWD

Typical peak reverse recovery current as a function of turn off gate resistor

$$I_{RM} = f(R_{goff})$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $I_c = 56$ A

T_j : — 25 °C
— 125 °C




Vincotech

10-F012NME080SH-M910F09
datasheet

Buck Switching Characteristics

figure 28. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_f/dt, di_r/dt = f(I_C)$




With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 4$ Ω

T_j : — 25 °C
— 125 °C

figure 29. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn off gate resistor
 $di_f/dt, di_r/dt = f(R_{goff})$



With an inductive load at


$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $I_C = 56$ A

T_j : — 25 °C
— 125 °C

figure 30. IGBT

Reverse bias safe operating area

$I_C = f(V_{CE})$



At $T_j = 125$ °C
 $R_{gon} = 4$ Ω
 $R_{goff} = 4$ Ω



Vincotech

10-F012NME080SH-M910F09 datasheet


Boost Switching Characteristics

figure 31.

IGBT

Typical switching energy losses as a function of collector current

$$E = f(I_C)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 4$ Ω
 $R_{goff} = 4$ Ω


T_j : 25 °C (blue)
125 °C (black)
150 °C (red)

figure 32.

IGBT

Typical switching energy losses as a function of gate resistor

$$E = f(R_g)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $I_C = 56$ A


T_j : 25 °C (blue)
125 °C (black)
150 °C (red)

figure 33.

FWD

Typical reverse recovered energy loss as a function of collector current

$$E_{rec} = f(I_C)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 4$ Ω


T_j : 25 °C (blue)
125 °C (black)
150 °C (red)

figure 34.

FWD

Typical reverse recovered energy loss as a function of gate resistor

$$E_{rec} = f(R_g)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $I_C = 56$ A

T_j : 25 °C (blue)
125 °C (black)
150 °C (red)



Vincotech

10-F012NME080SH-M910F09


datasheet

Boost Switching Characteristics

figure 35.

IGBT

Typical switching times as a function of collector current
 $t = f(I_C)$




With an inductive load at

$T_j = 150$ °C
 $V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 4$ Ω
 $R_{goff} = 4$ Ω

figure 36.

IGBT

Typical switching times as a function of gate resistor
 $t = f(R_g)$




With an inductive load at

$T_j = 150$ °C
 $V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $I_C = 56$ A

figure 37.

FWD

Typical reverse recovery time as a function of collector current
 $t_{rr} = f(I_C)$



With an inductive load at


$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 4$ Ω

T_j :
— 25 °C
— 125 °C
— 150 °C

figure 38.

FWD

Typical reverse recovery time as a function of IGBT turn off gate resistor
 $t_{rr} = f(R_{goff})$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $I_C = 56$ A

T_j :
— 25 °C
— 125 °C
— 150 °C



Vincotech

10-F012NME080SH-M910F09
datasheet


Boost Switching Characteristics

figure 39.

FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 4$ Ω


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 40.

FWD

Typical recovered charge as a function of turn off gate resistor

$$Q_r = f(R_{goff})$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $I_c = 56$ A


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 41.

FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 4$ Ω


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 42.

FWD

Typical peak reverse recovery current as a function of turn off gate resistor

$$I_{RM} = f(R_{goff})$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $I_c = 56$ A

T_j :
— 25 °C
— 125 °C
— 150 °C




Vincotech

10-F012NME080SH-M910F09
datasheet

Boost Switching Characteristics

figure 43. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_f/dt, di_r/dt = f(I_C)$




With an inductive load at

$V_{CE} = 350 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{goff} = 4 \Omega$

T_j :
— 25 °C
— 125 °C
— 150 °C

figure 44. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn off gate resistor
 $di_f/dt, di_r/dt = f(R_{goff})$



With an inductive load at


$V_{CE} = 350 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_C = 56 \text{ A}$

T_j :
— 25 °C
— 125 °C
— 150 °C

figure 45. IGBT

Reverse bias safe operating area

$I_C = f(V_{CE})$



At $T_j = 150 \text{ °C}$
 $R_{goff} = 4 \Omega$
 $R_{goff} = 4 \Omega$



Vincotech

Switching Definitions

figure 46. IGBT

Turn-off Switching Waveforms & definition of t_{doff} , t_{Eoff} (t_{Eoff} = integrating time for E_{off})




figure 47. IGBT

Turn-on Switching Waveforms & definition of t_{don} , t_{Eon} (t_{Eon} = integrating time for E_{on})




figure 48. IGBT

Turn-off Switching Waveforms & definition of t_f





figure 49. IGBT

Turn-on Switching Waveforms & definition of t_r





Vincotech

Switching Definitions

figure 50.

FWD

Turn-off Switching Waveforms & definition of t_{rr}





figure 51.

FWD

Turn-on Switching Waveforms & definition of t_{Qr} (t_{Qr} = integrating time for Q_r)





Vincotech

10-F012NME080SH-M910F09

datasheet

Ordering Code	
Version	Ordering Code
Without thermal paste	10-F012NME080SH-M910F09
With thermal paste (5,2 W/mK, PTM6000HV)	10-F012NME080SH-M910F09-/7/
With thermal paste (3,4 W/mK, PSX-P7)	10-F012NME080SH-M910F09-/3/

Marking						
Text	Name		Date code	UL & VIN	Lot	Serial
	NN-NNNNNNNNNNNNNN- TTTTTVV		WWYY	UL VIN	LLLLL	SSSS
Datamatrix	Type&Ver	Lot number	Serial	Date code		
	TTTTTVV	LLLLL	SSSS	WWYY		

Outline				
Pin table [mm]				Function
Pin	X	Y		
1	33,6	0		G2
2	30,7	0		S2
3	not assembled			
4	22	0		-DC
5	19,2	0		-DC
6	11,4	0		GND
7	0	0		S3
8	0	2,9		G3
9	0	9,9		Line
10	0	12,7		Line
11	0	15,5		Line
12	0	19,7		G4
13	0	22,6		S4
14	10,1	22,6		GND
15	17,9	22,6		+DC
16	20,8	22,6		+DC
17	not assembled			
18	30,7	22,6		S1
19	33,6	22,6		G1
20	33,6	14,8		NTC1
21	33,6	8,2		NTC2


Tolerance of pinpositions: $\pm 0,5\text{mm}$ at the end of pins
Dimension of coordinate axis is only offset without tolerance



Vincotech

10-F012NME080SH-M910F09
datasheet

Pinout




Identification

ID	Component	Voltage	Current	Function	Comment
T1, T2	IGBT	1200 V	80 A	Buck Switch	
D3, D4	FWD	600 V	60 A	Buck Diode	
T3, T4	IGBT	600 V	75 A	Boost Switch	
D1, D2	FWD	1200 V	35 A	Boost Diode	
NTC	Thermistor			Thermistor	



Vincotech

10-F012NME080SH-M910F09
datasheet

Packaging instruction				
Standard packaging quantity (SPQ) 135	>SPQ	Standard	<SPQ	Sample
Handling instruction				
Handling instructions for <i>flow 0</i> packages see vincotech.com website.				
Package data				
Package data for <i>flow 0</i> packages see vincotech.com website.				
Vincotech thermistor reference				
See Vincotech thermistor reference table at vincotech.com website.				
UL recognition and file number				
This device is certified according to UL 1557 standard, UL file number E192116. For more information see vincotech.com website.				

Document No.:	Date:	Modification:	Pages
10-F012NME080SH-M910F09-D3-14	12 Sep. 2021	New Datasheet format, module is unchanged Correct Thermal values Separate datasheet for pressfit pin version	

DISCLAIMER

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.