



Vincotech

10-FZ07LBA100SM01-L705L18

datasheet

flowNPFC 0

650 V / 100 A

Features

- Three-phase NPFC topology
- High efficient IGBT H5 technology
- Low inductive design
- Integrated Thermistor


Target applications

- Power Supply
- UPS


Types

- 10-FZ07LBA100SM01-L705L18

flow 0 12 mm housing



Schematic





Vincotech

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
-----------	--------	------------	-------	------

Buck Diode

Peak repetitive reverse voltage	V_{RRM}		650	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	84	A
Repetitive peak forward current	I_{FRM}	t_p limited by T_{jmax}	200	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	122	W
Maximum junction temperature	T_{jmax}		175	°C

Boost Switch

Collector-emitter voltage	V_{CES}		650	V
Collector current (DC current)	I_C	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	78	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	300	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	133	W
Gate-emitter voltage	V_{GES}		±20	V
Maximum junction temperature	T_{jmax}		175	°C

Boost Diode

Peak repetitive reverse voltage	V_{RRM}		1200	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	63	A
Surge (non-repetitive) forward current	I_{FSM}	Single Half Sine Wave, $t_p = 10\text{ ms}$ $T_j = 150\text{ °C}$	550	A
Surge current capability	I^2t		1513	A²s
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	122	W
Maximum junction temperature	T_{jmax}		175	°C

Capacitor (DC)

Maximum DC voltage	V_{MAX}		500	V
Operation Temperature	T_{op}		-55 ... 125	°C



Vincotech

10-FZ07LBA100SM01-L705L18
datasheet

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
-----------	--------	------------	-------	------

Module Properties

Thermal Properties

Storage temperature	T_{stg}		-40...+125	°C
Operation temperature under switching condition	T_{jop}		-40...+(T_{jmax} - 25)	°C

Isolation Properties

Isolation voltage	V_{isol}	DC Test Voltage* $t_p = 2\text{ s}$	6000	V
Isolation voltage	V_{isol}	AC Voltage $t_p = 1\text{ min}$	2500	V
Creepage distance			>12,7	mm
Clearance			9,15	mm
Comparative Tracking Index	CTI		≥ 200	

*100 % tested in production



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Buck Diode

Static

Forward voltage	V_F				100	25 150	1,18	1,78 1,57	1,82 ⁽¹⁾	V
Reverse leakage current	I_R	$V_r = 650$ V				25			1,2	μA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)						0,78		K/W
--	---------------	---------------------------------------	--	--	--	--	--	------	--	-----



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Boost Switch

Static

Gate-emitter threshold voltage	$V_{GE(th)}$	$V_{CE} = V_{GE}$			0,001	25	3,3	4	4,7	V
Collector-emitter saturation voltage	V_{CEsat}		15		100	25 125		1,63 1,78	2,22 ⁽¹⁾	V
Collector-emitter cut-off current	I_{CES}		0	650		25			80	µA
Gate-emitter leakage current	I_{GES}		20	0		25			240	nA
Internal gate resistance	r_g							None		Ω
Input capacitance	C_{ies}	$f = 1 \text{ Mhz}$	0	25		25		6000		pF
Output capacitance	C_{oes}							100		pF
Reverse transfer capacitance	C_{res}							22		pF
Gate charge	Q_g		15	520	100	25		240		nC

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4 \text{ W/mK}$ (PSX)						0,72		K/W
--	---------------	---	--	--	--	--	--	------	--	-----

Dynamic

Turn-on delay time	$t_{d(on)}$	$R_{gon} = 4 \Omega$ $R_{goff} = 4 \Omega$	-5/15	350	80	25 125 150		73,8 71,8 70,2		ns
Rise time	t_r					25 125 150		19,8 22,4 22		ns
Turn-off delay time	$t_{d(off)}$					25 125 150		162,4 176,4 179,8		ns
Fall time	t_f					25 125 150		6,11 9,5 8,91		ns
Turn-on energy (per pulse)	E_{on}	$Q_{tFWD}=4,92 \mu\text{C}$ $Q_{tFWD}=10,04 \mu\text{C}$ $Q_{tFWD}=12,44 \mu\text{C}$				25 125 150		2,75 3,6 3,93		mWs
Turn-off energy (per pulse)	E_{off}					25 125 150		0,297 0,515 0,594		mWs



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Boost Diode

Static

Forward voltage	V_F				100	25 125 150		2,24 2,45 2,38	2,52 ⁽¹⁾ 2,47 ⁽¹⁾	V
Reverse leakage current	I_R	$V_i = 1200$ V				25 150		8800	120 17700	μA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)						0,78		K/W
--	---------------	---------------------------------------	--	--	--	--	--	------	--	-----

Dynamic

Peak recovery current	I_{RRM}	$di/dt=4646$ A/μs $di/dt=3416$ A/μs $di/dt=3473$ A/μs	-5/15	350	80	25 125 150		78,52 106,41 116,57		A
Reverse recovery time	t_{rr}					25 125 150		119,16 219,11 243,11		ns
Recovered charge	Q_r					25 125 150		4,92 10,04 12,44		μC
Reverse recovered energy	E_{rec}					25 125 150		0,89 2,19 2,78		mWs
Peak rate of fall of recovery current	$(di_{rr}/dt)_{max}$					25 125 150		3514 3663 3540		A/μs



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Capacitor (DC)

Static

Capacitance	C	DC bias voltage = 0 V				25		150		nF
Tolerance							-10		10	%
Dissipation factor		$f = 1$ kHz				25		2,5		%

Thermistor

Static

Rated resistance	R					25		22		kΩ
Deviation of R_{100}	$\Delta_{R/R}$	$R_{100} = 1486 \Omega$				100	-12		14	%
Power dissipation	P							200		mW
Power dissipation constant	d					25		2		mW/K
B-value	$B_{(25/50)}$	Tol. ± 3 %						3950		K
B-value	$B_{(25/100)}$	Tol. ± 3 %						3998		K
Vincotech Thermistor Reference									B	

⁽¹⁾ Value at chip level

⁽²⁾ Only valid with pre-applied Vincotech thermal interface material.



Vincotech

10-FZ07LBA100SM01-L705L18

datasheet

Buck Diode Characteristics

figure 1. FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 2. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D =$	t_p / T
$R_{th(j-s)} =$	0,78 K/W
FWD thermal model values	
R (K/W)	τ (s)
5,76E-02	5,42E+00
8,79E-02	1,09E+00
2,14E-01	1,59E-01
2,31E-01	4,95E-02
1,16E-01	1,05E-02
3,20E-02	2,39E-03
4,19E-02	4,10E-04



Vincotech

10-FZ07LBA100SM01-L705L18


datasheet

Boost Switch Characteristics

figure 3. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $V_{GE} = 15 V$
 $T_j: 25 ^\circ C$ (blue line)
 $125 ^\circ C$ (red line)

figure 4. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $T_j = 125 ^\circ C$
 V_{GE} from 5 V to 18 V in steps of 1 V

figure 5. IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$




$t_p = 250 \mu s$
 $V_{CE} = 10 V$
 $T_j: 25 ^\circ C$ (blue line)
 $125 ^\circ C$ (red line)

figure 6. IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 0,715 K/W$
IGBT thermal model values

$R (K/W)$	$\tau (s)$
7,52E-02	1,73E+00
1,31E-01	2,44E-01
3,01E-01	6,32E-02
1,21E-01	1,39E-02
4,30E-02	3,50E-03
4,35E-02	3,33E-04



Vincotech

10-FZ07LBA100SM01-L705L18
datasheet


Boost Switch Characteristics

figure 7.

IGBT

Safe operating area

$$I_C = f(V_{CE})$$



$D = \text{single pulse}$

$T_s = 80 \text{ } ^\circ\text{C}$
 $V_{GE} = 15 \text{ V}$
 $T_j = T_{jmax}$



Vincotech

10-FZ07LBA100SM01-L705L18 datasheet

Boost Diode Characteristics

figure 8. FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 9. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D =$	t_p / T	
$R_{th(j-s)} =$	0,779	K/W
FWD thermal model values		
R (K/W)	τ (s)	
7,81E-02	1,59E+00	
1,93E-01	2,55E-01	
3,99E-01	7,68E-02	
7,07E-02	6,98E-03	
3,88E-02	9,88E-04	



Vincotech

10-FZ07LBA100SM01-L705L18
datasheet


Thermistor Characteristics

figure 10.

Thermistor

Typical NTC characteristic as function of temperature

$$R_T = f(T)$$





Vincotech

10-FZ07LBA100SM01-L705L18 datasheet


Boost Switching Characteristics

figure 11.

IGBT

Typical switching energy losses as a function of collector current

$$E = f(I_C)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $R_{gon} = 4$ Ω
 $R_{goff} = 4$ Ω


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 12.

IGBT

Typical switching energy losses as a function of gate resistor

$$E = f(R_g)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $I_C = 80$ A


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 13.

FWD

Typical reverse recovered energy loss as a function of collector current

$$E_{rec} = f(I_C)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $R_{gon} = 4$ Ω


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 14.

FWD

Typical reverse recovered energy loss as a function of gate resistor

$$E_{rec} = f(R_g)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $I_C = 80$ A

T_j :
— 25 °C
— 125 °C
— 150 °C



Vincotech

10-FZ07LBA100SM01-L705L18


datasheet

Boost Switching Characteristics

figure 15.

IGBT

Typical switching times as a function of collector current
 $t = f(I_c)$




With an inductive load at

$T_j = 150$ °C
 $V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $R_{gon} = 4$ Ω
 $R_{goff} = 4$ Ω

figure 16.

IGBT

Typical switching times as a function of gate resistor
 $t = f(R_g)$




With an inductive load at

$T_j = 150$ °C
 $V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $I_c = 80$ A

figure 17.

FWD

Typical reverse recovery time as a function of collector current
 $t_{rr} = f(I_c)$



With an inductive load at


$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $R_{gon} = 4$ Ω

T_j : — 25 °C
— 125 °C
— 150 °C

figure 18.

FWD

Typical reverse recovery time as a function of IGBT turn off gate resistor
 $t_{rr} = f(R_{goff})$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $I_c = 80$ A

T_j : — 25 °C
— 125 °C
— 150 °C



Vincotech

10-FZ07LBA100SM01-L705L18
datasheet


Boost Switching Characteristics

figure 19.

FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $R_{gon} = 4$ Ω


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 20.

FWD

Typical recovered charge as a function of turn off gate resistor

$$Q_r = f(R_{goff})$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $I_c = 80$ A


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 21.

FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $R_{gon} = 4$ Ω


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 22.

FWD

Typical peak reverse recovery current as a function of turn off gate resistor

$$I_{RM} = f(R_{goff})$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $I_c = 80$ A

T_j :
— 25 °C
— 125 °C
— 150 °C




Vincotech

10-FZ07LBA100SM01-L705L18
datasheet

Boost Switching Characteristics

figure 23. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_f/dt, di_r/dt = f(I_C)$



With an inductive load at


$V_{CE} = 350 \text{ V}$
 $V_{GE} = -5/15 \text{ V}$
 $R_{gon} = 4 \text{ } \Omega$

T_j :
 — 25 °C
 — 125 °C
 — 150 °C

figure 25. IGBT

Reverse bias safe operating area


$I_C = f(V_{CE})$



At $T_j = 150 \text{ } ^\circ\text{C}$
 $R_{gon} = 4 \text{ } \Omega$
 $R_{goff} = 4 \text{ } \Omega$

figure 24. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn off gate resistor
 $di_f/dt, di_r/dt = f(R_{goff})$



With an inductive load at

$V_{CE} = 350 \text{ V}$
 $V_{GE} = -5/15 \text{ V}$
 $I_C = 80 \text{ A}$

T_j :
 — 25 °C
 — 125 °C
 — 150 °C



Vincotech

10-FZ07LBA100SM01-L705L18 datasheet

Boost Switching Definitions

figure 26. IGBT

Turn-off Switching Waveforms & definition of t_{doff} , t_{Eoff} (t_{Eoff} = integrating time for E_{off})




figure 27. IGBT

Turn-on Switching Waveforms & definition of t_{don} , t_{Eon} (t_{Eon} = integrating time for E_{on})




figure 28. IGBT

Turn-off Switching Waveforms & definition of t_f





figure 29. IGBT

Turn-on Switching Waveforms & definition of t_r





Vincotech

Boost Switching Definitions

figure 30.

FWD

Turn-off Switching Waveforms & definition of t_{rr}





figure 31.

FWD

Turn-on Switching Waveforms & definition of t_{Qr} (t_{Qr} = integrating time for Q_r)





Vincotech

10-FZ07LBA100SM01-L705L18

datasheet

Ordering Code	
Version	Ordering Code
Without thermal paste	10-FZ07LBA100SM01-L705L18
With thermal paste (5,2 W/mK, PTM6000HV)	10-FZ07LBA100SM01-L705L18-/7/
With thermal paste (3,4 W/mK, PSX-P7)	10-FZ07LBA100SM01-L705L18-/3/

Marking						
	Text	Name	Date code	UL & VIN	Lot	Serial
		NN-NNNNNNNNNNNNNN- TTTTIV	WWYY	UL VIN	LLLLL	SSSS
	Datamatrix	Type&Ver	Lot number	Serial	Date code	
		TTTTTIV	LLLLL	SSSS	WWYY	

Outline																																																																																															
<p>Pin table [mm]</p> <table><thead><tr><th>Pin</th><th>X</th><th>Y</th><th>Function</th></tr></thead><tbody><tr><td>1</td><td></td><td></td><td>not assembled</td></tr><tr><td>2</td><td></td><td></td><td>not assembled</td></tr><tr><td>3</td><td></td><td></td><td>not assembled</td></tr><tr><td>4</td><td>19,2</td><td>0</td><td>-DC</td></tr><tr><td>5</td><td></td><td></td><td>not assembled</td></tr><tr><td>6</td><td>10,1</td><td>0</td><td>GND</td></tr><tr><td>7</td><td>2,8</td><td>0</td><td>Therm1</td></tr><tr><td>8</td><td>0</td><td>0</td><td>Therm2</td></tr><tr><td>9</td><td></td><td></td><td>not assembled</td></tr><tr><td>10</td><td>0</td><td>9,9</td><td>S2</td></tr><tr><td>11</td><td>0</td><td>12,7</td><td>G2</td></tr><tr><td>12</td><td></td><td></td><td>not assembled</td></tr><tr><td>13</td><td></td><td></td><td>not assembled</td></tr><tr><td>14</td><td></td><td></td><td>not assembled</td></tr><tr><td>15</td><td>10,1</td><td>22,6</td><td>GND</td></tr><tr><td>16</td><td></td><td></td><td>not assembled</td></tr><tr><td>17</td><td>19,2</td><td>22,6</td><td>+DC</td></tr><tr><td>18</td><td></td><td></td><td>not assembled</td></tr><tr><td>19</td><td></td><td></td><td>not assembled</td></tr><tr><td>20</td><td></td><td></td><td>not assembled</td></tr><tr><td>21</td><td>33,6</td><td>14,8</td><td>Ph</td></tr><tr><td>22</td><td>33,6</td><td>8,2</td><td>Ph</td></tr></tbody></table>				Pin	X	Y	Function	1			not assembled	2			not assembled	3			not assembled	4	19,2	0	-DC	5			not assembled	6	10,1	0	GND	7	2,8	0	Therm1	8	0	0	Therm2	9			not assembled	10	0	9,9	S2	11	0	12,7	G2	12			not assembled	13			not assembled	14			not assembled	15	10,1	22,6	GND	16			not assembled	17	19,2	22,6	+DC	18			not assembled	19			not assembled	20			not assembled	21	33,6	14,8	Ph	22	33,6	8,2	Ph
Pin	X	Y	Function																																																																																												
1			not assembled																																																																																												
2			not assembled																																																																																												
3			not assembled																																																																																												
4	19,2	0	-DC																																																																																												
5			not assembled																																																																																												
6	10,1	0	GND																																																																																												
7	2,8	0	Therm1																																																																																												
8	0	0	Therm2																																																																																												
9			not assembled																																																																																												
10	0	9,9	S2																																																																																												
11	0	12,7	G2																																																																																												
12			not assembled																																																																																												
13			not assembled																																																																																												
14			not assembled																																																																																												
15	10,1	22,6	GND																																																																																												
16			not assembled																																																																																												
17	19,2	22,6	+DC																																																																																												
18			not assembled																																																																																												
19			not assembled																																																																																												
20			not assembled																																																																																												
21	33,6	14,8	Ph																																																																																												
22	33,6	8,2	Ph																																																																																												
<p>Tolerance of pinpositions: ±0.5mm at the end of pins Dimension of coordinate axis is only offset without tolerance</p>																																																																																															




Vincotech

10-FZ07LBA100SM01-L705L18

datasheet

Pinout



Identification

ID	Component	Voltage	Current	Function	Comment
D55 , D57	FWD	650 V	100 A	Buck Diode	
T27, T25	IGBT	650 V	100 A	Boost Switch	
D25, D27	FWD	1200 V	100 A	Boost Diode	
C10, C20	Capacitor	500 V		Capacitor (DC)	
Rt	Thermistor			Thermistor	



Vincotech

Packaging instruction				
Standard packaging quantity (SPQ) 135	>SPQ	Standard	<SPQ	Sample

Handling instruction
Handling instructions for <i>flow 0</i> packages see vincotech.com website.

Package data
Package data for <i>flow 0</i> packages see vincotech.com website.

Vincotech thermistor reference
See Vincotech thermistor reference table at vincotech.com website.

UL recognition and file number
This device is certified according to UL 1557 standard, UL file number E192116. For more information see vincotech.com website.



Document No.:	Date:	Modification:	Pages
10-FZ07LBA100SM01-L705L18-D2-14	28 Sep. 2021	New Datasheet format, module is unchanged Update Boost Diode static measurements	

DISCLAIMER

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.