





Vincotech

10-F012PNA005M7-P848C29

datasheet

flow PIM 0		1200 V / 5 A
Features	flow 0 housing	
<ul style="list-style-type: none">• IGBT M7 with low V_{CEsat} and improved EMC behavior• Open emitter configuration• Compact and low inductive design• Built-in NTC		
Target applications	Schematic	
<ul style="list-style-type: none">• Industrial Drives		
Types		
<ul style="list-style-type: none">• 10-F012PNA005M7-P848C29		

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Condition	Value	Unit
Rectifier Diode				
Peak Repetitive Reverse Voltage	V_{RRM}		1600	V
Continuous (direct) forward current	I_F		25	A
Surge (non-repetitive) forward current	I_{FSM}	50 Hz Single Half Sine Wave $T_j = 150\text{ °C}$	200	A
Surge current capability	I^2t	$t_p = 10\text{ ms}$	200	A ² s
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	44	W
Maximum Junction Temperature	T_{jmax}		150	°C



Vincotech

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Condition	Value	Unit
Inverter Switch				
Collector-emitter voltage	V_{CES}		1200	V
Collector current	I_C		5	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	10	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	41	W
Gate-emitter voltage	V_{GES}		± 20	V
Maximum junction temperature	T_{jmax}		175	°C

Inverter Diode				
Peak repetitive reverse voltage	V_{RRM}		1200	V
Continuous (direct) forward current	I_F		5	A
Repetitive peak forward current	I_{FRM}	T_j limited by T_{jmax}	10	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	27	W
Maximum junction temperature	T_{jmax}		175	°C

Module Properties

Thermal Properties				
Storage temperature	T_{stg}		-40...+125	°C
Operation temperature under switching condition	T_{jop}		-40...($T_{jmax} - 25$)	°C

Isolation Properties				
Isolation voltage	V_{isol}	DC Test Voltage* $t_p = 2\text{ s}$	6000	V
		AC Voltage $t_p = 1\text{ min}$	2500	V
Creepage distance			min. 12,7	mm
Clearance		12 mm housing / 17 mm housing	9,29 / min. 12,7	mm
Comparative Tracking Index	CTI		> 200	

*100 % tested in production



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Value			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Rectifier Diode

Static

Forward voltage	V_F				30	25 125		1,22 1,21	1,8	V
Reverse leakage current	I_r			1600		25 145			50 1100	μA

Thermal

Thermal resistance junction to sink	$R_{th(j-s)}$	$\lambda_{paste} = 3,4 \text{ W/mK}$ (PSX)						1,59		K/W
-------------------------------------	---------------	---	--	--	--	--	--	------	--	-----



Characteristic Values

Parameter	Symbol	Conditions					Value			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Inverter Switch

Static

Gate-emitter threshold voltage	$V_{GE(th)}$	$V_{GE} = V_{CE}$			0,0005	25	5,4	6	6,6	V
Collector-emitter saturation voltage	V_{CEsat}		15		5	25 125 150		1,62 1,83 1,89	1,95	V
Collector-emitter cut-off current	I_{CES}		0	1200		25			50	μA
Gate-emitter leakage current	I_{GES}		20	0		25			500	nA
Internal gate resistance	r_g							none		Ω
Input capacitance	C_{ies}	0	10		25			1100		pF
Output capacitance	C_{oes}							57		
Reverse transfer capacitance	C_{res}							11		
Gate charge	Q_g		15	600	5	25		40		nC

Thermal

Thermal resistance junction to sink	$R_{th(j-s)}$	$\lambda_{paste} = 3,4 \text{ W/mK}$ (PSX)						2,30		K/W
-------------------------------------	---------------	---	--	--	--	--	--	------	--	-----

Dynamic

Turn-on delay time	$t_{d(on)}$	$R_{goff} = 64 \Omega$ $R_{gon} = 64 \Omega$	± 15	600	5	25 125 150		153 150 147		ns
Rise time	t_r					25 125 150		39 43 43		
Turn-off delay time	$t_{d(off)}$					25 125 150		154 176 181		
Fall time	t_f					25 125 150		89 115 111		
Turn-on energy (per pulse)	E_{on}	$Q_{rFWD} = 0,6 \mu\text{C}$ $Q_{rFWD} = 0,8 \mu\text{C}$ $Q_{rFWD} = 1 \mu\text{C}$				25 125 150		0,480 0,601 0,643		mWs
Turn-off energy (per pulse)	E_{off}					25 125 150		0,333 0,437 0,473		



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Value			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Inverter Diode

Static

Forward voltage	V_F				5	25 125 150		1,57 1,65 1,65	2,1	V
Reverse leakage current	I_R			1200		25			20	μA

Thermal

Thermal resistance junction to sink	$R_{th(j-s)}$	$\lambda_{paste} = 3,4 \text{ W/mK}$ (PSX)						3,50		K/W
-------------------------------------	---------------	---	--	--	--	--	--	------	--	-----

Dynamic

Peak recovery current	I_{RRM}	$di/dt = 83 \text{ A/}\mu\text{s}$ $di/dt = 111 \text{ A/}\mu\text{s}$ $di/dt = 92 \text{ A/}\mu\text{s}$	± 15	600	5	25 125 150		4 4 4		A
Reverse recovery time	t_{rr}					25 125 150		259 376 434		ns
Recovered charge	Q_r					25 125 150		0,551 0,773 0,985		μC
Reverse recovered energy	E_{rec}					25 125 150		0,186 0,273 0,378		mWs
Peak rate of fall of recovery current	$(di_{rr}/dt)_{max}$					25 125 150		46 24 25		A/μs

Thermistor

Rated resistance	R					25		22		kΩ
Deviation of R_{100}	$\Delta_{R/R}$	$R_{100} = 1484 \Omega$				100	-5		5	%
Power dissipation	P					25		5		mW
Power dissipation constant						25		1,5		mW/K
B-value	$B_{(25/50)}$	Tol. $\pm 1 \%$				25		3962		K
B-value	$B_{(25/100)}$	Tol. $\pm 1 \%$				25		4000		K
Vincotech NTC Reference									I	



Vincotech

Rectifier Diode Characteristics

figure 1. FWD
Typical forward characteristics





figure 2. FWD
Transient thermal impedance as a function of pulse width



Diode thermal model values

$R \text{ (K/W)}$	$\tau \text{ (s)}$
3,44E-02	9,66E+00
1,12E-01	1,22E+00
5,81E-01	1,45E-01
4,89E-01	5,05E-02
2,38E-01	9,26E-03
1,22E-01	1,79E-03
1,22E-01	1,79E-03




Vincotech

10-F012PNA005M7-P848C29 datasheet

Inverter Switch Characteristics

figure 1. IGBT


Typical output characteristics



$t_p = 250 \mu s$
 $V_{GE} = 15 V$
 $T_j: 25 \text{ } ^\circ C$ (dotted blue line)
 $125 \text{ } ^\circ C$ (solid black line)
 $150 \text{ } ^\circ C$ (dashed red line)

figure 2. IGBT


Typical output characteristics



$t_p = 250 \mu s$
 $T_j = 150 \text{ } ^\circ C$
 V_{GE} from 7 V to 17 V in steps of 1 V

figure 3. IGBT


Typical transfer characteristics



$t_p = 100 \mu s$
 $V_{CE} = 10 V$
 $T_j: 25 \text{ } ^\circ C$ (dotted blue line)
 $125 \text{ } ^\circ C$ (solid black line)
 $150 \text{ } ^\circ C$ (dashed red line)

figure 4. IGBT

Transient thermal impedance as function of pulse duration



$D = t_p / T$
 $R_{th(j-s)} = 2,30 \text{ K/W}$
IGBT thermal model values


$R \text{ (K/W)}$	$\tau \text{ (s)}$
6,25E-02	3,48E+00
1,37E-01	5,00E-01
7,38E-01	8,11E-02
5,28E-01	2,49E-02
3,84E-01	5,54E-03
2,39E-01	1,24E-03
2,13E-01	3,29E-04



Vincotech

Inverter Switch Characteristics

figure 5. IGBT
Safe operating area



$D =$ single pulse
 $T_s =$ 80 °C
 $V_{GE} =$ ±15 V
 $T_j =$ T_{jmax}



Vincotech

Inverter Diode Characteristics

figure 1. FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 2. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$$D = \frac{t_p}{T}$$
$$R_{th(j-s)} = 3,50 \text{ K/W}$$


FWD thermal model values

R (K/W)	τ (s)
8,03E-02	7,23E+00
2,34E-01	4,70E-01
1,33E+00	6,36E-02
7,92E-01	2,24E-02
5,71E-01	3,34E-03
4,85E-01	7,05E-04



Thermistor Characteristics

figure 1. Thermistor
Typical NTC characteristic as a function of temperature





Vincotech

Inverter Switching Characteristics

figure 1. IGBT

Typical switching energy losses as a function of collector current




figure 2. IGBT

Typical switching energy losses as a function of gate resistor




figure 3. FWD

Typical reverse recovered energy loss as a function of collector current





figure 4. FWD

Typical reverse recovered energy loss as a function of gate resistor






Vincotech

Inverter Switching Characteristics

figure 5. IGBT

Typical switching times as a function of collector current

$$t = f(I_C)$$




With an inductive load at

$T_j =$	150	°C
$V_{CE} =$	600	V
$V_{GE} =$	±15	V
$R_{gon} =$	64	Ω
$R_{goff} =$	64	Ω

figure 6. IGBT

Typical switching times as a function of gate resistor

$$t = f(R_g)$$




With an inductive load at

$T_j =$	150	°C
$V_{CE} =$	600	V
$V_{GE} =$	±15	V
$I_C =$	5	A

figure 7. FWD

Typical reverse recovery time as a function of collector current

$$t_{rr} = f(I_C)$$




At	$V_{CE} =$	600	V	$T_j:$	25 °C
	$V_{GE} =$	±15	V		125 °C	————
	$R_{gon} =$	64	Ω		150 °C	-----

figure 8. FWD

Typical reverse recovery time as a function of IGBT turn on gate resistor

$$t_{rr} = f(R_{gon})$$



At	$V_{CE} =$	600	V	$T_j:$	25 °C
	$V_{GE} =$	±15	V		125 °C	————
	$I_C =$	5	A		150 °C	-----




Vincotech

Inverter Switching Characteristics

figure 9. FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_C)$$




At $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 64$ Ω
 T_j : 25 °C (dotted blue)
125 °C (solid black)
150 °C (dashed red)

figure 10. FWD

Typical recovered charge as a function of IGBT turn on gate resistor

$$Q_r = f(R_{gon})$$




At $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_C = 5$ A
 T_j : 25 °C (dotted blue)
125 °C (solid black)
150 °C (dashed red)

figure 11. FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_C)$$




At $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 64$ Ω
 T_j : 25 °C (dotted blue)
125 °C (solid black)
150 °C (dashed red)

figure 12. FWD

Typical peak reverse recovery current as a function of IGBT turn on gate resistor

$$I_{RM} = f(R_{gon})$$



At $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_C = 5$ A
 T_j : 25 °C (dotted blue)
125 °C (solid black)
150 °C (dashed red)




Vincotech

Inverter Switching Characteristics

figure 13. FWD


Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_F/dt, di_{rr}/dt = f(I_C)$



At $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{g0n} = 64$ Ω
 $T_j = 25$ °C (dotted), 125 °C (solid), 150 °C (dashed)

figure 14. FWD

Typical rate of fall of forward and reverse recovery current as a function of IGBT turn on gate resistor
 $di_F/dt, di_{rr}/dt = f(R_{g0n})$




At $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_C = 5$ A
 $T_j = 25$ °C (dotted), 125 °C (solid), 150 °C (dashed)

figure 15. IGBT

Reverse bias safe operating area

$I_C = f(V_{CE})$



At $T_j = 175$ °C
 $R_{g0n} = 64$ Ω
 $R_{g0ff} = 64$ Ω



Vincotech

10-F012PNA005M7-P848C29
datasheet

Inverter Switching Definitions

General conditions

T_j	=	125 °C
R_{gon}	=	64 Ω
R_{goff}	=	64 Ω

figure 1. IGBT




figure 3. IGBT




figure 2. IGBT





figure 4. IGBT





Vincotech

Inverter Switching Characteristics

figure 5. IGBT




figure 6. IGBT





figure 7. FWD






Vincotech


Inverter Switching Characteristics

figure 8. FWD



I_F (100%) = 5 A
 Q_r (100%) = 0,87 μC
 t_{Qr} = 2,00 μs

figure 9. FWD





P_{rec} (100%) = 3,01 kW
 E_{rec} (100%) = 0,33 mJ
 t_{Erec} = 2,00 μs



10-F012PNA005M7-P848C29

datasheet

Vincotech

Ordering Code & Marking									
Version			Ordering Code						
without thermal paste 12 mm housing with solder pins			10-F012PNA005M7-P848C29						
<div><div>NN-NNNNNNNNNNNNNN TTTTTV WWYY UL VIN LLLLL SSSS</div><div></div><div></div></div>			Text	Name		Date code	UL & VIN	Lot	Serial
				NN-NNNNNNNNNNNNNN-TTTTTV		WWYY	UL VIN	LLLLL	SSSS
			Datamatrix	Type&Ver	Lot number	Serial	Date code		
				TTTTTV	LLLLL	SSSS	WWYY		

Pin table				Outline		
Pin	X	Y	Function			
1	25,5	2,7	Therm1			
2	25,5	0	Therm2			
3	22,8	0	DC-Rect			
4	Not assembled					
5	Not assembled					
6	13,5	0	G15			
7	10,8	0	DC-3			
8	8,1	0	G13			
9	5,4	0	DC-2			
10	2,7	0	G11			
11	0	0	DC-1			
12	0	19,8	G12			
13	0	22,5	Ph1			
14	7,5	19,8	G14			
15	7,5	22,5	Ph2			
16	15	19,8	G16			
17	15	22,5	Ph3			
18	22,8	22,5	DC+Inv			
19	25,5	22,5	DC+Rect			
20	Not assembled					
21	33,5	15	ACIn1			
22	33,5	7,5	ACIn2			
23	33,5	0	ACIn3			

1 ±0.05

213 ±0.5

112.5


16.75

Tolerance of pinpositions: ±0.5mm at the end of pins
Dimension of coordinate axis is only offset without tolerance



Vincotech

Pinout



Identification

ID	Component	Voltage	Current	Function	Comment
D31, D32, D33, D34, D35, D36	Rectifier	1600 V	25 A	Rectifier Diode	
T11, T12, T13, T14, T15, T16	IGBT	1200 V	5 A	Inverter Switch	
D11, D12, D13, D14, D15, D16	FWD	1200 V	5 A	Inverter Diode	
Rt	Thermistor	1200 V	5 A	NTC	




Vincotech

10-F012PNA005M7-P848C29
datasheet

Packaging instruction			
Standard packaging quantity (SPQ) 135	>SPQ	Standard	<SPQ Sample

Handling instruction
Handling instructions for <i>flow 0</i> packages see vincotech.com website.

Package data
Package data for <i>flow 0</i> packages see vincotech.com website.

UL recognition and file number
This device is certified according to UL 1557 standard, UL file number E192116. For more information see vincotech.com website. 

Document No.:	Date:	Modification:	Pages
10-F012PNA005M7-P848C29-D1-14	02 Jul. 2019		

DISCLAIMER

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.