



Vincotech

B0-EP12PMA100M7-PE89A68T

datasheet

flowPIM E3

1200 V / 100 A

Topology features

- Converter+Brake+Inverter
- Kelvin Emitter for improved switching performance
- Open Emitter configuration
- Temperature sensor

Component features

- Easy paralleling
- Low turn-off losses
- Low collector emitter saturation voltage
- Positive temperature coefficient
- Short tail current
- Switching optimized for EMC

Housing features

- Base isolation: Al_2O_3
- CTI600 housing material
- Compact, baseplate-less housing
- VINcoPress Technology
- Thermo-mechanical push-and-pull force relief
- Press-fit pin
- Reliable cold welding connection


Target applications

- General Purpose Drives
- Industrial Drives


Types

- B0-EP12PMA100M7-PE89A68T

flow E3 12 mm housing



Schematic





Vincotech

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
-----------	--------	------------	-------	------

Inverter Switch

Collector-emitter voltage	V_{CES}		1200	V
Collector current (DC current)	I_C	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	92	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	200	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	174	W
Gate-emitter voltage	V_{GES}		± 20	V
Short circuit ratings	t_{SC}	$V_{GE} = 15\text{ V}$, $V_{CC} = 800\text{ V}$ $T_j = 150\text{ °C}$	9,5	μs
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$

Inverter Diode

Peak repetitive reverse voltage	V_{RRM}		1200	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	70	A
Repetitive peak forward current	I_{FRM}	t_p limited by T_{jmax}	200	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	121	W
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$

Brake Switch

Collector-emitter voltage	V_{CES}		1200	V
Collector current (DC current)	I_C	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	60	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	100	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	124	W
Gate-emitter voltage	V_{GES}		± 20	V
Short circuit ratings	t_{SC}	$V_{GE} = 15\text{ V}$, $V_{CC} = 800\text{ V}$ $T_j = 150\text{ °C}$	9,5	μs
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$



Vincotech

B0-EP12PMA100M7-PE89A68T
datasheet

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Brake Diode				
Peak repetitive reverse voltage	V_{RRM}		1200	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	36	A
Repetitive peak forward current	I_{FRM}	t_p limited by T_{jmax}	50	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	71	W
Maximum junction temperature	T_{jmax}		175	°C

Rectifier Diode

Peak repetitive reverse voltage	V_{RRM}		1600	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	105	A
Surge (non-repetitive) forward current	I_{FSM}	Single Half Sine Wave, $t_p = 10\text{ ms}$ $T_j = 150\text{ °C}$	890	A
Surge current capability	I^2t		3960	A ² s
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	119	W
Maximum junction temperature	T_{jmax}		150	°C

Module Properties

Thermal Properties

Storage temperature	T_{stg}		-40...+125	°C
Operation temperature under switching condition	T_{jop}		-40...+($T_{jmax} - 25$)	°C

Isolation Properties

Isolation voltage	V_{isol}	DC Test Voltage* $t_p = 2\text{ s}$	6000	V
Isolation voltage	V_{isol}	AC Voltage $t_p = 1\text{ min}$	2500	V
Creepage distance			>12,7	mm
Clearance			9,85	mm
Comparative Tracking Index	CTI		≥ 600	

*100 % tested in production



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Inverter Switch

Static

Gate-emitter threshold voltage	$V_{GE(th)}$			10	0,01	25	5,4	6	6,6	V
Collector-emitter saturation voltage	$V_{CE(sat)}$		15		100	25 125 150		1,61 1,82 1,91	1,85 ⁽¹⁾	V
Collector-emitter cut-off current	I_{CES}		0	1200		25			100	µA
Gate-emitter leakage current	I_{GES}		20	0		25			200	nA
Internal gate resistance	r_g							None		Ω
Input capacitance	C_{ies}	0	10	25				21000		pF
Output capacitance	C_{oes}							700		pF
Reverse transfer capacitance	C_{res}							280		pF
Gate charge	Q_g	$V_{CC} = 600$ V	0/15		100	25		700		nC

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 5,2$ W/mK (PTM)						0,55		K/W
--	---------------	---------------------------------------	--	--	--	--	--	------	--	-----

Dynamic

Turn-on delay time	$t_{d(on)}$	$R_{gon} = 4$ Ω $R_{goff} = 4$ Ω	±15	600	100	25 125 150		171,48 170,07 170,74		ns
Rise time	t_r					25 125 150		43,95 48,13 48,68		ns
Turn-off delay time	$t_{d(off)}$					25 125 150		180,96 205,98 211,67		ns
Fall time	t_f					25 125 150		79,94 103,73 106,97		ns
Turn-on energy (per pulse)	E_{on}	$Q_{tFWD} = 8,03$ µC $Q_{tFWD} = 12,71$ µC $Q_{tFWD} = 14,17$ µC				25 125 150		8,11 10,32 10,98		mWs
Turn-off energy (per pulse)	E_{off}					25 125 150		7,27 9,97 10,68		mWs



Vincotech

B0-EP12PMA100M7-PE89A68T

datasheet

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Inverter Diode

Static

Forward voltage	V_F				100	25 125 150		1,82 1,96 1,97	2,1 ⁽¹⁾	V
Reverse leakage current	I_R	$V_i = 1200$ V				25			40	μA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 5,2$ W/mK (PTM)						0,79		K/W
--	---------------	---------------------------------------	--	--	--	--	--	------	--	-----

Dynamic

Peak recovery current	I_{RM}	$di/dt=1914$ A/μs $di/dt=1727$ A/μs $di/dt=1638$ A/μs	± 15	600	100	25 125 150		65,79 72,68 75,18		A
Reverse recovery time	t_{rr}					25 125 150		276,98 420,88 458,99		ns
Recovered charge	Q_r					25 125 150		8,03 12,71 14,17		μC
Reverse recovered energy	E_{rec}					25 125 150		2,85 4,83 5,43		mWs
Peak rate of fall of recovery current	$(di_{rr}/dt)_{max}$					25 125 150		704,7 494,51 472,28		A/μs



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Brake Switch

Static

Gate-emitter threshold voltage	$V_{GE(th)}$			10	0,005	25	5,4	6	6,6	V
Collector-emitter saturation voltage	$V_{CE(sat)}$		15		50	25 125 150		1,55 1,77 1,83	1,9 ⁽¹⁾	V
Collector-emitter cut-off current	I_{CES}		0	1200		25			0,09	mA
Gate-emitter leakage current	I_{GES}		20	0		25			0,5	μA
Internal gate resistance	r_g							None		Ω
Input capacitance	C_{ies}	0	10	25				10000		pF
Output capacitance	C_{oes}							350		pF
Reverse transfer capacitance	C_{res}							130		pF
Gate charge	Q_g	$V_{CC} = 600$ V	0/15		50	25		380		nC

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 5,2$ W/mK (PTM)						0,77		K/W
--	---------------	---------------------------------------	--	--	--	--	--	------	--	-----

Dynamic

Turn-on delay time	$t_{d(on)}$	$R_{gon} = 8$ Ω $R_{goff} = 8$ Ω	0/15	700	50	25 125 150		77,46 74,38 72,91		ns
Rise time	t_r					25 125 150		43,86 46,64 47,83		ns
Turn-off delay time	$t_{d(off)}$					25 125 150		293,47 329,61 338,69		ns
Fall time	t_f					25 125 150		91,96 120,11 133,54		ns
Turn-on energy (per pulse)	E_{on}	$Q_{tFWD} = 3,21$ μC $Q_{tFWD} = 4,61$ μC $Q_{tFWD} = 5,06$ μC				25 125 150		4,2 5,04 5,32		mWs
Turn-off energy (per pulse)	E_{off}					25 125 150		4,58 6,44 6,94		mWs



Vincotech

B0-EP12PMA100M7-PE89A68T

datasheet

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Brake Diode

Static

Forward voltage	V_F				25	25 125 150		1,63 1,7 1,69	2,1 ⁽¹⁾	V
Reverse leakage current	I_R	$V_i = 1200$ V				25			35	µA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 5,2$ W/mK (PTM)						1,34		K/W
--	---------------	---------------------------------------	--	--	--	--	--	------	--	-----

Dynamic

Peak recovery current	I_{RM}	$di/dt=1004$ A/µs $di/dt=898$ A/µs $di/dt=920$ A/µs	0/15	700	50	25 125 150		28,04 30,12 30,87		A
Reverse recovery time	t_{rr}					25 125 150		244,53 350,17 380,42		ns
Recovered charge	Q_r					25 125 150		3,21 4,61 5,06		µC
Reverse recovered energy	E_{rec}					25 125 150		1,36 2,07 2,29		mWs
Peak rate of fall of recovery current	$(di_{rr}/dt)_{max}$					25 125 150		299,69 211,89 204,8		A/µs



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]		Min	Typ	Max	

Rectifier Diode

Static

Forward voltage	V_F			60	25 125 150			1,06 0,99 0,97	1,5 ⁽¹⁾	V
Reverse leakage current	I_R	$V_i = 1600$ V			25 150				100 2	μA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 5,2$ W/mK (PTM)						0,59		K/W
--	---------------	---------------------------------------	--	--	--	--	--	------	--	-----

Thermistor

Static

Rated resistance	R				25			22		kΩ
Deviation of R_{100}	$\Delta_{R/R}$	$R_{100} = 1484$ Ω			100	-5		5		%
Power dissipation	P				25			130		mW
Power dissipation constant	d				25			1,5		mW/K
B-value	$B_{(25/50)}$	Tol. ± 1 %						3962		K
B-value	$B_{(25/100)}$	Tol. ± 1 %						4000		K
Vincotech Thermistor Reference									I	

⁽¹⁾ Value at chip level

⁽²⁾ Only valid with pre-applied Vincotech thermal interface material.



Vincotech

B0-EP12PMA100M7-PE89A68T


datasheet

Inverter Switch Characteristics

figure 1. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $V_{GE} = 15 V$
 $T_j:$ 25 °C, 125 °C, 150 °C

figure 2. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $T_j = 150 \text{ } ^\circ C$
 V_{GE} from 7 V to 17 V in steps of 1 V

figure 3. IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$




$t_p = 250 \mu s$
 $V_{CE} = 10 V$
 $T_j:$ 25 °C, 125 °C, 150 °C

figure 4. IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 0,545 \text{ K/W}$
IGBT thermal model values

$R \text{ (K/W)}$	$\tau \text{ (s)}$
5,00E-02	2,85E+00
9,49E-02	5,03E-01
2,74E-01	9,38E-02
8,25E-02	3,17E-02
2,20E-02	5,55E-03
2,13E-02	5,96E-04



Vincotech

B0-EP12PMA100M7-PE89A68T


datasheet

Inverter Switch Characteristics

figure 5. IGBT

Safe operating area

$$I_C = f(V_{CE})$$




$D =$ single pulse
 $T_s = 80$ °C
 $V_{GE} = 15$ V
 $T_j = T_{jmax}$

figure 6. IGBT

Gate voltage vs gate charge

$$V_{GE} = f(Q_g)$$



$I_C = 100$ A
 $T_j = 25$ °C



Vincotech

Inverter Diode Characteristics

figure 7.

FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 8.

FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D =$	t_p / T	
$R_{th(j-s)} =$	0,787	K/W
FWD thermal model values		
R (K/W)	τ (s)	
4,05E-02	3,25E+00	
9,02E-02	5,38E-01	
3,71E-01	8,95E-02	
1,97E-01	3,04E-02	
5,23E-02	4,59E-03	
3,58E-02	6,26E-04	



Vincotech

B0-EP12PMA100M7-PE89A68T datasheet


Brake Switch Characteristics

figure 9.

IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $V_{GE} = 15 V$
 T_j : 25 °C, 125 °C, 150 °C

figure 10.

IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $T_j = 150 \text{ °C}$
 V_{GE} from 7 V to 17 V in steps of 1 V

figure 11.

IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$




$t_p = 250 \mu s$
 $V_{CE} = 10 V$
 T_j : 25 °C, 125 °C, 150 °C

figure 12.

IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 0,766 \text{ K/W}$
IGBT thermal model values

$R \text{ (K/W)}$	$\tau \text{ (s)}$
4,42E-02	4,45E+00
9,11E-02	9,15E-01
2,73E-01	1,28E-01
2,59E-01	4,34E-02
6,73E-02	6,94E-03
3,15E-02	6,91E-04



Vincotech

B0-EP12PMA100M7-PE89A68T

datasheet


Brake Switch Characteristics

figure 13.

IGBT

Safe operating area

$$I_C = f(V_{CE})$$



$D =$ single pulse

$T_s = 80$ °C

$V_{GE} = 15$ V


$T_j = T_{jmax}$

figure 14.

IGBT

Gate voltage vs gate charge

$$V_{GE} = f(Q_g)$$



$I_C = 50$ A

$T_j = 25$ °C



Vincotech


Brake Diode Characteristics

figure 15.

FWD

Typical forward characteristics

$$I_F = f(V_F)$$



$t_p = 250 \mu s$


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 16.

FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D =$	t_p / T
$R_{th(j-s)} =$	1,335 K/W
FWD thermal model values	
R (K/W)	τ (s)
7,90E-02	2,29E+00
1,38E-01	2,89E-01
5,15E-01	5,53E-02
3,34E-01	1,22E-02
1,30E-01	2,48E-03
1,40E-01	3,42E-04



Vincotech


Rectifier Diode Characteristics

figure 17.

Rectifier

Typical forward characteristics

$$I_F = f(V_F)$$



$t_p = 250 \mu s$


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 18.

Rectifier

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D =$	t_p / T
$R_{th(j-s)} =$	0,587 K/W
Rectifier thermal model values	
R (K/W)	τ (s)
1,76E-02	1,19E+01
1,01E-01	1,09E+00
3,04E-01	1,13E-01
1,25E-01	2,75E-02
4,00E-02	1,55E-03



Vincotech

B0-EP12PMA100M7-PE89A68T
datasheet

Thermistor Characteristics

figure 19.

Thermistor

Typical NTC characteristic as function of temperature

$$R_T = f(T)$$





Vincotech

B0-EP12PMA100M7-PE89A68T datasheet


Inverter Switching Characteristics

figure 20.

IGBT

Typical switching energy losses as a function of collector current

$$E = f(I_C)$$



With an inductive load at

$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 4 \text{ } \Omega$
 $R_{goff} = 4 \text{ } \Omega$


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 22.

FWD

Typical reverse recovered energy loss as a function of collector current

$$E_{rec} = f(I_C)$$



With an inductive load at

$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 4 \text{ } \Omega$


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 21.

IGBT

Typical switching energy losses as a function of IGBT turn on gate resistor

$$E = f(R_g)$$



With an inductive load at

$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_C = 100 \text{ A}$


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 23.

FWD

Typical reverse recovered energy loss as a function of IGBT turn on gate resistor

$$E_{rec} = f(R_g)$$



With an inductive load at

$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_C = 100 \text{ A}$

T_j :
— 25 °C
— 125 °C
— 150 °C



Vincotech

B0-EP12PMA100M7-PE89A68T

datasheet


Inverter Switching Characteristics

figure 24.

IGBT

Typical switching times as a function of collector current

$$t = f(I_C)$$



With an inductive load at


$T_j =$	150	°C
$V_{CE} =$	600	V
$V_{GE} =$	±15	V
$R_{gon} =$	4	Ω
$R_{goff} =$	4	Ω

figure 26.

FWD

Typical reverse recovery time as a function of collector current

$$t_{rr} = f(I_C)$$



With an inductive load at

$V_{CE} =$	600	V
$V_{GE} =$	±15	V
$R_{gon} =$	4	Ω


$T_j:$ — 25 °C
— 125 °C
— 150 °C

figure 25.

IGBT

Typical switching times as a function of IGBT turn on gate resistor

$$t = f(R_g)$$



With an inductive load at


$T_j =$	150	°C
$V_{CE} =$	600	V
$V_{GE} =$	±15	V
$I_C =$	100	A

figure 27.

FWD

Typical reverse recovery time as a function of IGBT turn on gate resistor

$$t_{rr} = f(R_{gon})$$



With an inductive load at

$V_{CE} =$	600	V
$V_{GE} =$	±15	V
$I_C =$	100	A

$T_j:$ — 25 °C
— 125 °C
— 150 °C



Vincotech

B0-EP12PMA100M7-PE89A68T datasheet


Inverter Switching Characteristics

figure 28.

FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at


$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 4$ Ω
 T_j : 25 °C (blue), 125 °C (black), 150 °C (red)

figure 30.

FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at


$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 4$ Ω
 T_j : 25 °C (blue), 125 °C (black), 150 °C (red)

figure 29.

FWD

Typical recovered charge as a function of IGBT turn on gate resistor

$$Q_r = f(R_{gon})$$



With an inductive load at


$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 100$ A
 T_j : 25 °C (blue), 125 °C (black), 150 °C (red)

figure 31.

FWD

Typical peak reverse recovery current as a function of IGBT turn on gate resistor

$$I_{RM} = f(R_{gon})$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 100$ A
 T_j : 25 °C (blue), 125 °C (black), 150 °C (red)




Vincotech

B0-EP12PMA100M7-PE89A68T datasheet

Inverter Switching Characteristics

figure 32. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_f/dt, di_r/dt = f(I_C)$




With an inductive load at

$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 4 \text{ } \Omega$
 $T_j = 25 \text{ } ^\circ\text{C}$
 $T_j = 125 \text{ } ^\circ\text{C}$
 $T_j = 150 \text{ } ^\circ\text{C}$

figure 33. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn on gate resistor
 $di_f/dt, di_r/dt = f(R_{gon})$




With an inductive load at

$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_C = 100 \text{ A}$
 $T_j = 25 \text{ } ^\circ\text{C}$
 $T_j = 125 \text{ } ^\circ\text{C}$
 $T_j = 150 \text{ } ^\circ\text{C}$

figure 34. IGBT

Reverse bias safe operating area

$I_C = f(V_{CE})$



At $T_j = 150 \text{ } ^\circ\text{C}$
 $R_{gon} = 4 \text{ } \Omega$
 $R_{goff} = 4 \text{ } \Omega$



Vincotech

B0-EP12PMA100M7-PE89A68T datasheet


Brake Switching Characteristics

figure 35.

IGBT

Typical switching energy losses as a function of collector current

$$E = f(I_c)$$



With an inductive load at

$V_{CE} = 700 \text{ V}$
 $V_{GE} = 0/15 \text{ V}$
 $R_{gon} = 8 \text{ } \Omega$
 $R_{goff} = 8 \text{ } \Omega$


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 36.

IGBT

Typical switching energy losses as a function of IGBT turn on gate resistor

$$E = f(R_g)$$



With an inductive load at

$V_{CE} = 700 \text{ V}$
 $V_{GE} = 0/15 \text{ V}$
 $I_c = 50 \text{ A}$


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 37.

FWD

Typical reverse recovered energy loss as a function of collector current

$$E_{rec} = f(I_c)$$



With an inductive load at

$V_{CE} = 700 \text{ V}$
 $V_{GE} = 0/15 \text{ V}$
 $R_{gon} = 8 \text{ } \Omega$


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 38.

FWD

Typical reverse recovered energy loss as a function of IGBT turn on gate resistor

$$E_{rec} = f(R_g)$$



With an inductive load at

$V_{CE} = 700 \text{ V}$
 $V_{GE} = 0/15 \text{ V}$
 $I_c = 50 \text{ A}$

T_j :
— 25 °C
— 125 °C
— 150 °C



Vincotech

B0-EP12PMA100M7-PE89A68T
datasheet

Brake Switching Characteristics

figure 39. IGBT

Typical switching times as a function of collector current
 $t = f(I_C)$




figure 40. IGBT

Typical switching times as a function of IGBT turn on gate resistor
 $t = f(R_g)$




figure 41. FWD

Typical reverse recovery time as a function of collector current
 $t_{rr} = f(I_C)$





figure 42. FWD

Typical reverse recovery time as a function of IGBT turn on gate resistor
 $t_{rr} = f(R_{gon})$





Vincotech

B0-EP12PMA100M7-PE89A68T
datasheet


Brake Switching Characteristics

figure 43.

FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at

$V_{CE} = 700$ V
 $V_{GE} = 0/15$ V
 $R_{gon} = 8$ Ω


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 45.

FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at

$V_{CE} = 700$ V
 $V_{GE} = 0/15$ V
 $R_{gon} = 8$ Ω


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 44.

FWD

Typical recovered charge as a function of IGBT turn on gate resistor

$$Q_r = f(R_{gon})$$



With an inductive load at

$V_{CE} = 700$ V
 $V_{GE} = 0/15$ V
 $I_c = 50$ A


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 46.

FWD

Typical peak reverse recovery current as a function of IGBT turn on gate resistor

$$I_{RM} = f(R_{gon})$$



With an inductive load at

$V_{CE} = 700$ V
 $V_{GE} = 0/15$ V
 $I_c = 50$ A

T_j :
— 25 °C
— 125 °C
— 150 °C




Vincotech

Brake Switching Characteristics

figure 47. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_f/dt, di_r/dt = f(I_C)$




With an inductive load at

$V_{CE} = 700$ V
 $V_{GE} = 0/15$ V
 $R_{gon} = 8$ Ω

T_j :
 — 25 °C
 — 125 °C
 — 150 °C

figure 48. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn on gate resistor
 $di_f/dt, di_r/dt = f(R_{gon})$



With an inductive load at


$V_{CE} = 700$ V
 $V_{GE} = 0/15$ V
 $I_C = 50$ A

T_j :
 — 25 °C
 — 125 °C
 — 150 °C

figure 49. IGBT

Reverse bias safe operating area

$I_C = f(V_{CE})$



At $T_j = 150$ °C
 $R_{gon} = 8$ Ω
 $R_{goff} = 8$ Ω



Vincotech

B0-EP12PMA100M7-PE89A68T datasheet

Switching Definitions

figure 50. IGBT

Turn-off Switching Waveforms & definition of t_{doff} , t_{Eoff} (t_{Eoff} = integrating time for E_{off})




figure 51. IGBT

Turn-on Switching Waveforms & definition of t_{don} , t_{Eon} (t_{Eon} = integrating time for E_{on})



figure 52. IGBT

Turn-off Switching Waveforms & definition of t_f





figure 53. IGBT

Turn-on Switching Waveforms & definition of t_r





Vincotech

Switching Definitions

figure 54.

FWD

Turn-off Switching Waveforms & definition of t_{rr}



figure 55.

FWD

Turn-on Switching Waveforms & definition of t_{Qr} (t_{Qr} = integrating time for Q_r)





datasheet

Ordering Code	
Version	Ordering Code
Without thermal paste	B0-EP12PMA100M7-PE89A68T
With thermal paste (5,2 W/mK, PTM6000HV)	B0-EP12PMA100M7-PE89A68T-/7/

Marking							

Outline							
Pin table [mm]							
Pin	X	Y	Function	35	0	41,6	DC+R
1	72,16	3,2	BR	36	0	38,4	DC+R
2	72,16	0	BR	37	9,6	48	DC-R
3	59,36	3,2	G16	38	12,8	48	DC-R
4	59,36	0	E16	39	9,6	44,8	DC-R
5	52,96	3,2	PH3	40	12,8	44,8	DC-R
6	56,16	3,2	PH3	41	19,2	48	E11
7	52,96	0	PH3	42	19,2	44,8	G11
8	56,16	0	PH3	43	22,4	48	DC-1
9	43,36	6,4	G14	44	22,4	44,8	DC-1
10	43,36	3,2	E14	45	22,4	41,6	DC-1
11	40,16	6,4	PH2	46	32	48	DC+1
12	40,16	3,2	PH2	47	32	44,8	DC+1
13	40,16	0	PH2	48	32	41,6	DC+1
14	43,36	0	PH2	49	40,16	48	DC+2
15	32	3,2	G12	50	43,36	48	DC+2
16	32	0	E12	51	40,16	44,8	DC+2
17	25,6	3,2	PH1	52	43,36	44,8	DC+2
18	28,8	3,2	PH1	53	56,16	48	DC-2
19	25,6	0	PH1	54	59,36	48	DC-2
20	28,8	0	PH1	55	62,56	48	DC-2
21	12,8	3,2	ACIN3	56	65,76	48	DC-3
22	16	3,2	ACIN3	57	68,96	48	DC-3
23	12,8	0	ACIN3	58	72,16	48	DC-3
24	16	0	ACIN3	59	68,96	44,8	E15
25	0	3,2	ACIN2	60	68,96	41,6	G15
26	3,2	3,2	ACIN2	61	72,16	44,8	DC-BR
27	0	0	ACIN2	62	72,16	41,6	DC-BR
28	3,2	0	ACIN2	63	72,16	32	E27
29	0	25,6	ACIN1	64	72,16	28,8	G27
30	0	22,4	ACIN1	65	72,16	16	T1
31	0	19,2	ACIN1	66	72,16	12,8	T2
32	0	16	ACIN1	67	52,96	28,8	E13
33	0	48	DC+R	68	56,16	28,8	G13
34	0	44,8	DC+R				

center of press-fit pin head

pin head type "T", PCB plated through-hole $\Phi 1\text{mm}$ $+0,09/-0,06$

for further PCB design rules refer to the latest handling instruction

Tolerance of propositions: $\pm 0.4\text{mm}$ at the end of the pins

Dimension of coordinate axis is only offset without tolerance




Vincotech

B0-EP12PMA100M7-PE89A68T

datasheet

Pinout




Identification

ID	Component	Voltage	Current	Function	Comment
T11, T12, T13, T14, T15, T16	IGBT	1200 V	100 A	Inverter Switch	
D11, D12, D13, D14, D15, D16	FWD	1200 V	100 A	Inverter Diode	
T27	IGBT	1200 V	50 A	Brake Switch	
D27	FWD	1200 V	25 A	Brake Diode	
D31, D32, D33, D34, D35, D36	Rectifier	1600 V	60 A	Rectifier Diode	
Rt	Thermistor			Thermistor	



Vincotech

B0-EP12PMA100M7-PE89A68T
datasheet

Packaging instruction				
Standard packaging quantity (SPQ) 40	>SPQ	Standard	<SPQ	Sample
Handling instruction				
Handling instructions for <i>flow</i> E3 packages see vincotech.com website.				
Package data				
Package data for <i>flow</i> E3 packages see vincotech.com website.				
Vincotech thermistor reference				
See Vincotech thermistor reference table at vincotech.com website.				
UL recognition and file number				
This device is certified according to UL 1557 standard, UL file number E192116. For more information see vincotech.com website.				

Document No.:	Date:	Modification:	Pages
B0-EP12PMA100M7-PE89A68T-D1-14	1 Sep. 2022		

DISCLAIMER

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.