



Vincotech

10-FZ122PB100SH-M819F28

datasheet

flowPHASE 0 + NTC

1200 V / 100 A

Features

- High efficiency fast IGBT4 HS half-bridge
- Full current FWD
- Thermistor


Target applications

- Industrial Drives
- Power Supply
- Solar
- UPS
- Welding & Cutting


Types

- 10-FZ122PB100SH-M819F28

flow 0 12 mm housing



Schematic





Vincotech

10-FZ122PB100SH-M819F28
datasheet

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
-----------	--------	------------	-------	------

Half-Bridge Switch - Hi side

Collector-emitter voltage	V_{CES}		1200	V
Collector current (DC current)	I_C	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	87	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	300	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	201	W
Gate-emitter voltage	V_{GES}		± 20	V
Short circuit ratings	t_{SC}	$V_{GE} = 15\text{ V}$, $V_{CC} = 800\text{ V}$ $T_j = 150\text{ °C}$	10	μs
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$

Half-Bridge Switch - Lo side

Collector-emitter voltage	V_{CES}		1200	V
Collector current (DC current)	I_C	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	87	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	300	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	201	W
Gate-emitter voltage	V_{GES}		± 20	V
Short circuit ratings	t_{SC}	$V_{GE} = 15\text{ V}$, $V_{CC} = 800\text{ V}$ $T_j = 150\text{ °C}$	10	μs
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$

Half-Bridge Diode - Hi side

Peak repetitive reverse voltage	V_{RRM}		1200	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	64	A
Surge (non-repetitive) forward current	I_{FSM}	Single Half Sine Wave, $t_p = 10\text{ ms}$ $T_j = 150\text{ °C}$	550	A
Surge current capability	I^2t		1513	A^2s
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	122	W
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$



Vincotech

10-FZ122PB100SH-M819F28
datasheet

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Half-Bridge Diode - Lo side				
Peak repetitive reverse voltage	V_{RRM}		1200	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	64	A
Surge (non-repetitive) forward current	I_{FSM}	Single Half Sine Wave, $t_p = 10\text{ ms}$ $T_j = 150\text{ °C}$	550	A
Surge current capability	I^2t		1513	A ² s
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	122	W
Maximum junction temperature	T_{jmax}		175	°C

Module Properties

Thermal Properties

Storage temperature	T_{stg}		-40...+125	°C
Operation temperature under switching condition	T_{jop}		-40...+($T_{jmax} - 25$)	°C

Isolation Properties

Isolation voltage	V_{isol}	DC Test Voltage* $t_p = 2\text{ s}$	6000	V
Isolation voltage	V_{isol}	AC Voltage $t_p = 1\text{ min}$	2500	V
Creepage distance			>12,7	mm
Clearance			9,12	mm
Comparative Tracking Index	CTI		> 200	

*100 % tested in production



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]		Min	Typ	Max	

Half-Bridge Switch - Hi side

Static

Gate-emitter threshold voltage	$V_{GE(th)}$	$V_{CE} = V_{GE}$			0,0038	25	5,1	5,8	6,4	V
Collector-emitter saturation voltage	$V_{CE(sat)}$		15		100	25 150	1,78	1,95 2,39	2,42 ⁽¹⁾	V
Collector-emitter cut-off current	I_{CES}		0	1200		25			1,3	µA
Gate-emitter leakage current	I_{GES}		20	0		25			120	nA
Internal gate resistance	r_g							7,5		Ω
Input capacitance	C_{ies}	$f = 1 \text{ Mhz}$	0	25	25			6150		pF
Reverse transfer capacitance	C_{res}							345		pF
Gate charge	Q_g		15		0	25		800		nC

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4 \text{ W/mK}$ (PSX)						0,47		K/W
--	---------------	---	--	--	--	--	--	------	--	-----

Dynamic

Turn-on delay time	$t_{d(on)}$	$R_{gon} = 1 \Omega$ $R_{goff} = 1 \Omega$	± 15	600	100	25 125 150		129,2 143,2 145,2		ns
Rise time	t_r					25 125 150		27,6 30,4 33,8		ns
Turn-off delay time	$t_{d(off)}$					25 125 150		214,2 268,6 282		ns
Fall time	t_f					25 125 150		26,36 66,55 76,62		ns
Turn-on energy (per pulse)	E_{on}					25 125 150		4,85 7,4 8,5		mWs
Turn-off energy (per pulse)	E_{off}					25 125 150		4,12 6,2 6,89		mWs



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]		Min	Typ	Max	

Half-Bridge Switch - Lo side

Static

Gate-emitter threshold voltage	$V_{GE(th)}$	$V_{CE} = V_{GE}$			0,0038	25	5,1	5,8	6,4	V
Collector-emitter saturation voltage	V_{CEsat}		15		100	25 150	1,78	1,95 2,39	2,42 ⁽¹⁾	V
Collector-emitter cut-off current	I_{CES}		0	1200		25			1,3	µA
Gate-emitter leakage current	I_{GES}		20	0		25			120	nA
Internal gate resistance	r_g							7,5		Ω
Input capacitance	C_{ies}	$f = 1 \text{ Mhz}$	0	25	25			6150		pF
Reverse transfer capacitance	C_{res}							345		pF
Gate charge	Q_g		15		0	25		800		nC

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4 \text{ W/mK}$ (PSX)						0,47		K/W
--	---------------	---	--	--	--	--	--	------	--	-----

Dynamic

Turn-on delay time	$t_{d(on)}$	$R_{gon} = 1 \Omega$ $R_{goff} = 1 \Omega$	± 15	600	100	25 125 150		129,2 143,2 145,2		ns
Rise time	t_r					25 125 150		27,6 30,4 33,8		ns
Turn-off delay time	$t_{d(off)}$					25 125 150		214,2 268,6 282		ns
Fall time	t_f					25 125 150		26,36 66,55 76,62		ns
Turn-on energy (per pulse)	E_{on}					25 125 150		4,85 7,4 8,5		mWs
Turn-off energy (per pulse)	E_{off}					25 125 150		4,12 6,2 6,89		mWs



Vincotech

10-FZ122PB100SH-M819F28
datasheet

Characteristic Values

Parameter	Symbol	Conditions						Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]		Min	Typ	Max	

Half-Bridge Diode - Hi side

Static

Forward voltage	V_F				100	25 125 150		2,3 2,38 2,31	2,52 ⁽¹⁾ 2,47 ⁽¹⁾	V
Reverse leakage current	I_R	$V_i = 1200$ V				25 150		8800	120 17700	µA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)						0,78		K/W
--	---------------	---------------------------------------	--	--	--	--	--	------	--	-----

Dynamic

Peak recovery current	I_{RRM}	$di/dt=3967$ A/µs $di/dt=3671$ A/µs $di/dt=3881$ A/µs	± 15	600	100	25 125 150		100,94 119,83 129,79		A
Reverse recovery time	t_{rr}					25 125 150		157,77 336,7 369,56		ns
Recovered charge	Q_r					25 125 150		6,66 13,25 16,16		µC
Reverse recovered energy	E_{rec}					25 125 150		2,52 5,3 6,44		mWs
Peak rate of fall of recovery current	$(di_{rr}/dt)_{max}$					25 125 150		4584 3088 2896		A/µs



Vincotech

10-FZ122PB100SH-M819F28
datasheet

Characteristic Values

Parameter	Symbol	Conditions						Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]		Min	Typ	Max	

Half-Bridge Diode - Lo side

Static

Forward voltage	V_F				100	25 125 150		2,3 2,38 2,31	2,52 ⁽¹⁾ 2,47 ⁽¹⁾	V
Reverse leakage current	I_R	$V_i = 1200$ V				25 150		8800	120 17700	µA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)						0,78		K/W
--	---------------	---------------------------------------	--	--	--	--	--	------	--	-----

Dynamic

Peak recovery current	I_{RRM}	$di/dt=3967$ A/µs $di/dt=3671$ A/µs $di/dt=3881$ A/µs	± 15	600	100	25 125 150		100,94 119,83 129,79		A
Reverse recovery time	t_{rr}					25 125 150		157,77 336,7 369,56		ns
Recovered charge	Q_r					25 125 150		6,66 13,25 16,16		µC
Reverse recovered energy	E_{rec}					25 125 150		2,52 5,3 6,44		mWs
Peak rate of fall of recovery current	$(di_{rr}/dt)_{max}$					25 125 150		4584 3088 2896		A/µs



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Thermistor

Static

Rated resistance	R					25		22		kΩ
Deviation of R_{100}	$\Delta_{R/R}$	$R_{100} = 1484 \Omega$				100	-5		5	%
Power dissipation	P							5		mW
Power dissipation constant	d					25		1,5		mW/K
B-value	$B_{(25/50)}$	Tol. $\pm 1 \%$						3962		K
B-value	$B_{(25/100)}$	Tol. $\pm 1 \%$						4000		K
Vincotech Thermistor Reference									I	

⁽¹⁾ Value at chip level

⁽²⁾ Only valid with pre-applied Vincotech thermal interface material.



Vincotech

10-FZ122PB100SH-M819F28
datasheet


Half-Bridge Switch - Hi side Characteristics

figure 1.

IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$



$t_p = 250 \mu s$
 $V_{GE} = 15 V$


T_j : — 25 °C
— 150 °C

figure 2.

IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$



$t_p = 250 \mu s$
 $T_j = 150 \text{ °C}$


V_{GE} from 8 V to 17 V in steps of 1 V

figure 3.

IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$



$t_p = 250 \mu s$
 $V_{CE} = 10 V$


T_j : — 25 °C
— 150 °C

figure 4.

IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 0,473 K/W$

IGBT thermal model values

$R (K/W)$	$\tau (s)$
8,95E-02	1,40E+00
1,91E-01	1,86E-01
1,52E-01	5,52E-02
2,19E-02	5,98E-03
1,89E-02	6,39E-04



Vincotech


10-FZ122PB100SH-M819F28
datasheet

Half-Bridge Switch - Hi side Characteristics

figure 5. IGBT

Safe operating area

$$I_C = f(V_{CE})$$



$D = \text{single pulse}$

$T_s = 80 \text{ } ^\circ\text{C}$
 $V_{GE} = 15 \text{ V}$
 $T_j = T_{jmax}$



Vincotech

10-FZ122PB100SH-M819F28


datasheet

Half-Bridge Switch - Lo side Characteristics

figure 6. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $V_{GE} = 15 V$
 $T_j: 25 ^\circ C$ (blue line)
 $150 ^\circ C$ (red line)

figure 7. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $T_j = 150 ^\circ C$
 V_{GE} from 8 V to 17 V in steps of 1 V

figure 8. IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$




$t_p = 250 \mu s$
 $V_{CE} = 10 V$
 $T_j: 25 ^\circ C$ (blue line)
 $150 ^\circ C$ (red line)

figure 9. IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 0,473 K/W$
 IGBT thermal model values

$R (K/W)$	$\tau (s)$
8,95E-02	1,40E+00
1,91E-01	1,86E-01
1,52E-01	5,52E-02
2,19E-02	5,98E-03
1,89E-02	6,39E-04



Vincotech

10-FZ122PB100SH-M819F28
datasheet


Half-Bridge Switch - Lo side Characteristics

figure 10.

IGBT

Safe operating area

$$I_C = f(V_{CE})$$



D = single pulse

$T_s = 80$ °C
 $V_{GE} = 15$ V
 $T_j = T_{jmax}$



Vincotech

10-FZ122PB100SH-M819F28


datasheet

Half-Bridge Diode - Hi side Characteristics

figure 11. FWD

Typical forward characteristics

$$I_F = f(V_F)$$




$t_p = 250 \mu s$

T_j : 25 °C, 125 °C, 150 °C

figure 12. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$

$R_{th(j-s)} = 0,779 \text{ K/W}$

FWD thermal model values

R (K/W)	τ (s)
$7,81E-02$	$1,59E+00$
$1,93E-01$	$2,55E-01$
$3,99E-01$	$7,68E-02$
$7,07E-02$	$6,98E-03$
$3,88E-02$	$9,88E-04$



Vincotech

10-FZ122PB100SH-M819F28 datasheet


Half-Bridge Diode - Lo side Characteristics

figure 13.

FWD

Typical forward characteristics

$$I_F = f(V_F)$$



$t_p = 250 \mu s$


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 14.

FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 0,779 \text{ K/W}$
FWD thermal model values

$R \text{ (K/W)}$	$\tau \text{ (s)}$
7,81E-02	1,59E+00
1,93E-01	2,55E-01
3,99E-01	7,68E-02
7,07E-02	6,98E-03
3,88E-02	9,88E-04



Vincotech


10-FZ122PB100SH-M819F28
datasheet

Thermistor Characteristics

figure 15. Thermistor

Typical NTC characteristic as function of temperature

$$R_T = f(T)$$





Vincotech

10-FZ122PB100SH-M819F28
datasheet


Half-Bridge Switching Characteristics - Hi side

figure 16.

IGBT

Typical switching energy losses as a function of collector current

$$E = f(I_c)$$



With an inductive load at

$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 1 \text{ } \Omega$
 $R_{goff} = 1 \text{ } \Omega$


T_j : 25 °C
125 °C
150 °C

figure 17.

IGBT

Typical switching energy losses as a function of gate resistor

$$E = f(R_g)$$



With an inductive load at

$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 100 \text{ A}$


T_j : 25 °C
125 °C
150 °C

figure 18.

FWD

Typical reverse recovered energy loss as a function of collector current

$$E_{rec} = f(I_c)$$



With an inductive load at

$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 1 \text{ } \Omega$


T_j : 25 °C
125 °C
150 °C

figure 19.

FWD

Typical reverse recovered energy loss as a function of gate resistor

$$E_{rec} = f(R_g)$$



With an inductive load at

$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 100 \text{ A}$

T_j : 25 °C
125 °C
150 °C



Vincotech

10-FZ122PB100SH-M819F28
datasheet

Half-Bridge Switching Characteristics - Hi side

figure 20.

IGBT

Typical switching times as a function of collector current

$$t = f(I_C)$$




figure 21.

IGBT

Typical switching times as a function of gate resistor

$$t = f(R_g)$$




figure 22.

FWD

Typical reverse recovery time as a function of collector current

$$t_{rr} = f(I_C)$$





figure 23.

FWD

Typical reverse recovery time as a function of IGBT turn off gate resistor

$$t_{rr} = f(R_{goff})$$





Vincotech

10-FZ122PB100SH-M819F28
datasheet


Half-Bridge Switching Characteristics - Hi side

figure 24.

FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 1$ Ω


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 26.

FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 1$ Ω


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 25.

FWD

Typical recovered charge as a function of turn off gate resistor

$$Q_r = f(R_{goff})$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 100$ A


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 27.

FWD

Typical peak reverse recovery current as a function of turn off gate resistor

$$I_{RM} = f(R_{goff})$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 100$ A

T_j :
— 25 °C
— 125 °C
— 150 °C




Vincotech

10-FZ122PB100SH-M819F28
datasheet

Half-Bridge Switching Characteristics - Hi side

figure 28. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_f/dt, di_r/dt = f(I_C)$



With an inductive load at


$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 1 \text{ } \Omega$

T_j :
— 25 °C
— 125 °C
— 150 °C

figure 30. IGBT

Reverse bias safe operating area


$I_C = f(V_{CE})$



At $T_j = 150 \text{ } ^\circ\text{C}$
 $R_{gon} = 1 \text{ } \Omega$
 $R_{goff} = 1 \text{ } \Omega$

figure 29. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn off gate resistor
 $di_f/dt, di_r/dt = f(R_{goff})$



With an inductive load at

$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_C = 100 \text{ A}$

T_j :
— 25 °C
— 125 °C
— 150 °C



Vincotech

10-FZ122PB100SH-M819F28
datasheet


Half-Bridge Switching Characteristics - Lo side

figure 31.

IGBT

Typical switching energy losses as a function of collector current

$$E = f(I_C)$$



With an inductive load at

$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 1 \text{ } \Omega$
 $R_{goff} = 1 \text{ } \Omega$


T_j : 25 °C
125 °C
150 °C

figure 32.

IGBT

Typical switching energy losses as a function of gate resistor

$$E = f(R_g)$$



With an inductive load at

$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_C = 100 \text{ A}$


T_j : 25 °C
125 °C
150 °C

figure 33.

FWD

Typical reverse recovered energy loss as a function of collector current

$$E_{rec} = f(I_C)$$



With an inductive load at

$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 1 \text{ } \Omega$


T_j : 25 °C
125 °C
150 °C

figure 34.

FWD

Typical reverse recovered energy loss as a function of gate resistor

$$E_{rec} = f(R_g)$$



With an inductive load at

$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_C = 100 \text{ A}$

T_j : 25 °C
125 °C
150 °C



Vincotech

10-FZ122PB100SH-M819F28
datasheet

Half-Bridge Switching Characteristics - Lo side

figure 35.

IGBT

Typical switching times as a function of collector current
 $t = f(I_c)$




figure 36.

IGBT

Typical switching times as a function of gate resistor
 $t = f(R_g)$




figure 37.

FWD

Typical reverse recovery time as a function of collector current
 $t_{rr} = f(I_c)$





figure 38.

FWD

Typical reverse recovery time as a function of IGBT turn off gate resistor
 $t_{rr} = f(R_{goff})$





Vincotech

10-FZ122PB100SH-M819F28
datasheet


Half-Bridge Switching Characteristics - Lo side

figure 39.

FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 1$ Ω


T_j : 25 °C (blue)
125 °C (black)
150 °C (red)

figure 41.

FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 1$ Ω


T_j : 25 °C (blue)
125 °C (black)
150 °C (red)

figure 40.

FWD

Typical recovered charge as a function of turn off gate resistor

$$Q_r = f(R_{goff})$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 100$ A


T_j : 25 °C (blue)
125 °C (black)
150 °C (red)

figure 42.

FWD

Typical peak reverse recovery current as a function of turn off gate resistor

$$I_{RM} = f(R_{goff})$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 100$ A

T_j : 25 °C (blue)
125 °C (black)
150 °C (red)




Vincotech

10-FZ122PB100SH-M819F28
datasheet

Half-Bridge Switching Characteristics - Lo side

figure 43. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_f/dt, di_r/dt = f(I_C)$



With an inductive load at


$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{goff} = 1 \text{ } \Omega$

T_j :
— 25 °C
— 125 °C
— 150 °C

figure 44. FWD

Reverse bias safe operating area


$I_C = f(V_{CE})$



At $T_j = 150 \text{ } ^\circ\text{C}$
 $R_{goff} = 1 \text{ } \Omega$
 $R_{goff} = 1 \text{ } \Omega$

figure 44. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn off gate resistor
 $di_f/dt, di_r/dt = f(R_{goff})$



With an inductive load at

$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_C = 100 \text{ A}$

T_j :
— 25 °C
— 125 °C
— 150 °C



Vincotech

10-FZ122PB100SH-M819F28 datasheet

Switching Definitions

figure 46. IGBT

Turn-off Switching Waveforms & definition of t_{doff} , t_{Eoff} (t_{Eoff} = integrating time for E_{off})




figure 47. IGBT

Turn-on Switching Waveforms & definition of t_{don} , t_{Eon} (t_{Eon} = integrating time for E_{on})




figure 48. IGBT

Turn-off Switching Waveforms & definition of t_f





figure 49. IGBT

Turn-on Switching Waveforms & definition of t_r





Vincotech

Switching Definitions

figure 50.

FWD

Turn-off Switching Waveforms & definition of t_{rr}





figure 51.

FWD

Turn-on Switching Waveforms & definition of t_{Qr} (t_{Qr} = integrating time for Q_r)





Vincotech

10-FZ122PB100SH-M819F28

datasheet

Ordering Code	
Version	Ordering Code
Without thermal paste	10-FZ122PB100SH-M819F28
With thermal paste (5,2 W/mK, PTM6000HV)	10-FZ122PB100SH-M819F28-/7/
With thermal paste (3,4 W/mK, PSX-P7)	10-FZ122PB100SH-M819F28-/3/

Marking						
	Text	Name	Date code	UL & VIN	Lot	Serial
		NN-NNNNNNNNNNNNNN- TTTTUV	WWYY	UL VIN	LLLL	SSSS
	Datamatrix	Type&Ver	Lot number	Serial	Date code	
		TTTTTUV	LLLL	SSSS	WWYY	

Outline				
Pin table [mm]				
Pin	X	Y	Function	
1	0	0	DC-	
2	0	2,3	DC-	
3	0	4,6	DC-	
4	0	6,9	DC-	
5	0	15,6	DC+	
6	0	17,9	DC+	
7	0	20,2	DC+	
8	0	22,5	DC+	
9	13,85	16,45	G12	
10	16,75	16,45	S12	
11	33,5	11,5	Ph	
12	33,5	9,2	Ph	
13	33,5	6,9	Ph	
14	33,5	4,6	Ph	
15	33,5	2,3	Ph	
16	33,5	0	Ph	
17	13,85	13,55	Ph	
18	19,55	4,95	S11	
19	19,55	7,85	G11	
20	33,5	22,5	Therm1	
21	26,1	22,5	Therm2	

Tolerance of pinpositions: ±0.5mm at the end of pins
Dimension of coordinate axis is only offset without tolerance




Vincotech

10-FZ122PB100SH-M819F28

datasheet

Pinout



Identification

ID	Component	Voltage	Current	Function	Comment
T11-a	IGBT	1200 V	100 A	Half-Bridge Switch - Lo side	
T12-a	IGBT	1200 V	100 A	Half-Bridge Switch - Hi side	
D11-a	FWD	1200 V	100 A	Half-Bridge Diode - Hi side	
D12-a	FWD	1200 V	100 A	Half-Bridge Diode - Lo side	
Rt	NTC			Thermistor	



Vincotech

10-FZ122PB100SH-M819F28
datasheet

Packaging instruction				
Standard packaging quantity (SPQ) 135	>SPQ	Standard	<SPQ	Sample

Handling instruction
Handling instructions for <i>flow 0</i> packages see vincotech.com website.

Package data
Package data for <i>flow 0</i> packages see vincotech.com website.

Vincotech thermistor reference
See Vincotech thermistor reference table at vincotech.com website.

UL recognition and file number
This device is certified according to UL 1557 standard, UL file number E192116. For more information see vincotech.com website.



Document No.:	Date:	Modification:	Pages
10-FZ122PB100SH-M819F28-D2-14	7 Sep. 2021	Diode static characteristics corrected New datasheet format, module is unchanged	

DISCLAIMER

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.