



Vincotech

10-EZ126PA035RA-L859F88T

datasheet

flowPACK E1

1200 V / 35 A

Topology features

- Open Emitter configuration
- Temperature sensor
- Inverter
- Low side Kelvin Emitter for improved switching performance

Component features

- Easy paralleling
- Low collector emitter saturation voltage
- Low turn-off losses

Housing features

- Base isolation: Al_2O_3
- Convex shaped substrate for superior thermal contact
- Compact housing
- CTI600 housing material
- Thermo-mechanical push-and-pull force relief
- Press-fit pin
- Reliable cold welding connection

Target applications

- Elevator Drives
- Industrial Drives
- Servo Drives


Types

- 10-EZ126PA035RA-L859F88T

flow E1 12 mm housing



Schematic





Vincotech

10-EZ126PA035RA-L859F88T
datasheet

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Inverter Switch				
Collector-emitter voltage	V_{CES}		1200	V
Collector current (DC current)	I_C	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	46	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	105	A
Turn off safe operating area		$T_j = 150\text{ °C}$, $V_{CE} = 1200\text{ V}$	105	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	117	W
Gate-emitter voltage	V_{GES}		± 30	V
Short circuit ratings	t_{SC}	$V_{GE} = 15\text{ V}$, $V_{CC} = 800\text{ V}$ $T_j = 150\text{ °C}$	8	μs
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$

Inverter Diode

Peak repetitive reverse voltage	V_{RRM}		1200	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	48	A
Repetitive peak forward current	I_{FRM}	t_p limited by T_{jmax}	120	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	95	W
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$

Module Properties

Thermal Properties

Storage temperature	T_{stg}		$-40...+125$	$^{\circ}\text{C}$
Operation temperature under switching condition	T_{jop}		$-40...+(T_{jmax} - 25)$	$^{\circ}\text{C}$

Isolation Properties

Isolation voltage	V_{isol}	DC Test Voltage* $t_p = 2\text{ s}$	6000	V
Creepage distance			$> 12,7$	mm
Clearance			8,62	mm
Comparative Tracking Index	CTI		≥ 600	

*100 % tested in production



Vincotech

10-EZ126PA035RA-L859F88T

datasheet

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Inverter Switch

Static

Gate-emitter threshold voltage	$V_{GE(th)}$			5	0,004	25	5,5	6,3	7,1	V
Collector-emitter saturation voltage	V_{CEsat}		15		35	25 125 150		1,7 2,03 2,11	1,95 ⁽¹⁾	V
Collector-emitter cut-off current	I_{CES}		0	1200		25			10	µA
Gate-emitter leakage current	I_{GES}		30	0		25			500	nA
Internal gate resistance	r_g							None		Ω
Input capacitance	C_{ies}	$f = 1 \text{ Mhz}$	0	30		25		5565		pF
Output capacitance	C_{oes}							129		pF
Reverse transfer capacitance	C_{res}							46		pF
Gate charge	Q_g		0/15	600	35	25		215		nC

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 5,2 \text{ W/mK}$ (PTM)						0,81		K/W
----------------------------------------------------	---------------	-----------------------------------------------	--	--	--	--	--	------	--	-----

Dynamic

Turn-on delay time	$t_{d(on)}$	$R_{gon} = 16 \Omega$ $R_{goff} = 16 \Omega$	± 15	600	35	25 125 150		196,99 195,13 192,81		ns
Rise time	t_r					25 125 150		42,51 50,38 53,11		ns
Turn-off delay time	$t_{d(off)}$					25 125 150		198,71 220,86 227,34		ns
Fall time	t_f					25 125 150		125,53 151,32 160,03		ns
Turn-on energy (per pulse)	E_{on}	$Q_{tFWD}=2,25 \mu C$ $Q_{tFWD}=4,61 \mu C$ $Q_{tFWD}=5,55 \mu C$				25 125 150		3,02 4,29 4,73		mWs
Turn-off energy (per pulse)	E_{off}					25 125 150		3,08 3,91 4,25		mWs



Vincotech

10-EZ126PA035RA-L859F88T

datasheet

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Inverter Diode

Static

Forward voltage	V_F				40	25 125 150		1,61 1,79 1,78	2,1 ⁽¹⁾	V
Reverse leakage current	I_R	$V_i = 1200$ V				25			10	µA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 5,2$ W/mK (PTM)						1		K/W
----------------------------------------------------	---------------	---------------------------------------	--	--	--	--	--	---	--	-----

Dynamic

Peak recovery current	I_{RM}	$di/dt=701$ A/µs $di/dt=543$ A/µs $di/dt=577$ A/µs	± 15	600	35	25 125 150		24,4 27,05 28,47		A
Reverse recovery time	t_{rr}					25 125 150		231,89 430,1 487,75		ns
Recovered charge	Q_r					25 125 150		2,25 4,61 5,55		µC
Reverse recovered energy	E_{rec}					25 125 150		0,677 1,63 2		mWs
Peak rate of fall of recovery current	$(di_{rr}/dt)_{max}$					25 125 150		489,21 164,95 121,8		A/µs



Vincotech

10-EZ126PA035RA-L859F88T
datasheet

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Thermistor

Static

Rated resistance	R					25		5		k Ω
Deviation of R100	$\Delta_{R/R}$	$R_{100} = 499 \Omega$				100	3,2		3,3	%
Power dissipation	P					25		130		mW
Power dissipation constant	d					25		1,3		mW/K
B-value	$B_{(25/50)}$	Tol. $\pm 1 \%$						3380		K
Vincotech Thermistor Reference									V	

⁽¹⁾ Value at chip level

⁽²⁾ Only valid with pre-applied Vincotech thermal interface material.



Vincotech

10-EZ126PA035RA-L859F88T

datasheet

Inverter Switch Characteristics

figure 1. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




figure 2. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




figure 3. IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$





figure 4. IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$





Vincotech


10-EZ126PA035RA-L859F88T
datasheet

Inverter Switch Characteristics

figure 5. IGBT

Safe operating area

$I_C = f(V_{CE})$



$D = \text{single pulse}$

$T_s = 80 \text{ } ^\circ\text{C}$

$V_{GE} = 15 \text{ V}$

$T_j = T_{jmax}$



Vincotech

10-EZ126PA035RA-L859F88T datasheet

Inverter Diode Characteristics

figure 6. FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 7. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$





Vincotech

10-EZ126PA035RA-L859F88T
datasheet


Thermistor Characteristics

figure 8.

Thermistor

Typical NTC characteristic as function of temperature

$$R_T = f(T)$$





Vincotech

10-EZ126PA035RA-L859F88T datasheet


Inverter Switching Characteristics

figure 9.

IGBT

Typical switching energy losses as a function of collector current

$$E = f(I_c)$$



With an inductive load at

$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 16 \text{ } \Omega$
 $R_{goff} = 16 \text{ } \Omega$


T_j : $25 \text{ } ^\circ\text{C}$ (blue)
 $125 \text{ } ^\circ\text{C}$ (black)
 $150 \text{ } ^\circ\text{C}$ (red)

figure 10.

IGBT

Typical switching energy losses as a function of IGBT turn on gate resistor

$$E = f(R_g)$$



With an inductive load at

$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 35 \text{ A}$


T_j : $25 \text{ } ^\circ\text{C}$ (blue)
 $125 \text{ } ^\circ\text{C}$ (black)
 $150 \text{ } ^\circ\text{C}$ (red)

figure 11.

FWD

Typical reverse recovered energy loss as a function of collector current

$$E_{rec} = f(I_c)$$



With an inductive load at

$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 16 \text{ } \Omega$


T_j : $25 \text{ } ^\circ\text{C}$ (blue)
 $125 \text{ } ^\circ\text{C}$ (black)
 $150 \text{ } ^\circ\text{C}$ (red)

figure 12.

FWD

Typical reverse recovered energy loss as a function of IGBT turn on gate resistor

$$E_{rec} = f(R_g)$$



With an inductive load at

$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 35 \text{ A}$

T_j : $25 \text{ } ^\circ\text{C}$ (blue)
 $125 \text{ } ^\circ\text{C}$ (black)
 $150 \text{ } ^\circ\text{C}$ (red)



Vincotech


10-EZ126PA035RA-L859F88T datasheet

Inverter Switching Characteristics

figure 13.

IGBT

Typical switching times as a function of collector current
 $t = f(I_c)$




With an inductive load at

$T_j = 150$ °C
 $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 16$ Ω
 $R_{goff} = 16$ Ω

figure 14.

IGBT

Typical switching times as a function of IGBT turn on gate resistor
 $t = f(R_g)$




With an inductive load at

$T_j = 150$ °C
 $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 35$ A

figure 15.

FWD

Typical reverse recovery time as a function of collector current
 $t_{rr} = f(I_c)$



With an inductive load at


$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 16$ Ω

T_j :
— 25 °C
— 125 °C
— 150 °C

figure 16.

FWD

Typical reverse recovery time as a function of IGBT turn on gate resistor
 $t_{rr} = f(R_{gon})$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 35$ A

T_j :
— 25 °C
— 125 °C
— 150 °C



Vincotech

10-EZ126PA035RA-L859F88T datasheet


Inverter Switching Characteristics

figure 17.

FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 16$ Ω


T_j : 25 °C
125 °C
150 °C

figure 19.

FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 16$ Ω


T_j : 25 °C
125 °C
150 °C

figure 18.

FWD

Typical recovered charge as a function of IGBT turn on gate resistor

$$Q_r = f(R_{gon})$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 35$ A


T_j : 25 °C
125 °C
150 °C

figure 20.

FWD

Typical peak reverse recovery current as a function of IGBT turn on gate resistor

$$I_{RM} = f(R_{gon})$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 35$ A

T_j : 25 °C
125 °C
150 °C



Vincotech


10-EZ126PA035RA-L859F88T

datasheet

Inverter Switching Characteristics

figure 21. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_f/dt, di_r/dt = f(I_c)$




With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 16$ Ω
 $T_j = 25$ °C
 $T_j = 125$ °C
 $T_j = 150$ °C

figure 22. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn on gate resistor
 $di_f/dt, di_r/dt = f(R_{gon})$




With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 35$ A
 $T_j = 25$ °C
 $T_j = 125$ °C
 $T_j = 150$ °C

figure 23. IGBT

Reverse bias safe operating area

$I_c = f(V_{CE})$



At $T_j = 150$ °C
 $R_{gon} = 16$ Ω
 $R_{goff} = 16$ Ω



Vincotech

10-EZ126PA035RA-L859F88T datasheet

Inverter Switching Definitions

figure 24. IGBT

Turn-off Switching Waveforms & definition of t_{doff} , t_{Eoff} (t_{Eoff} = integrating time for E_{off})




figure 25. IGBT

Turn-on Switching Waveforms & definition of t_{don} , t_{Eon} (t_{Eon} = integrating time for E_{on})




figure 26. IGBT

Turn-off Switching Waveforms & definition of t_f





figure 27. IGBT

Turn-on Switching Waveforms & definition of t_r





Vincotech

Inverter Switching Definitions

figure 28.

FWD

Turn-off Switching Waveforms & definition of t_{rr}





figure 29.

FWD



Turn-on Switching Waveforms & definition of t_{Qr} (t_{Qr} = integrating time for Q_r)





datasheet

Ordering Code	
Version	Ordering Code
Without thermal paste	10-EZ126PA035RA-L859F88T
With thermal paste (5,2 W/mK, PTM6000HV)	10-EZ126PA035RA-L859F88T-/7/

Marking							
	Text	Name		Date code	UL & VIN	Lot	Serial
		NN-NNNNNNNNNNNNN- TTTTTIVV		WWYY	UL VIN	LLLLL	SSSS
		Datamatrix	Type&Ver	Lot number	Serial	Date code	
TTTTTIVV			LLLLL	SSSS	WWYY		

Outline

Pin table [mm]			
Pin	X	Y	Function
1	12,8	9,6	DC+
2	16	9,6	DC+
3	22,4	9,6	Therm1
4	25,6	9,6	Therm2
5	32	9,6	DC-2
6	32	6,4	S13
7	32	3,2	DC-1
8	32	0	S11
9	28,8	0	G11
10	6,4	0	Ph1
11	3,2	0	Ph1
12	0	0	G12
13	0	6,4	G14
14	0	16	Ph2
15	0	19,2	Ph2
16	0	25,6	G16
17	3,2	25,6	Ph3
18	6,4	25,6	Ph3
19	28,8	25,6	G15
20	32	25,6	S15
21	32	22,4	DC-3
22	32	16	G13

center of press-fit pinhead
for connection parameter see the handling instruction

128 ±0,1
64 ±0,5


128
64
X
Y

Tolerance of pinpositions: ±0,4mm at the end of pins
Dimension of coordinate axis is only offset without tolerance



Vincotech

Pinout




Identification

ID	Component	Voltage	Current	Function	Comment
T11, T12, T13, T14, T15, T16	IGBT	1200 V	35 A	Inverter Switch	
D11, D12, D13, D14, D15, D16	FWD	1200 V	40 A	Inverter Diode	
Rt	NTC			Thermistor	



Vincotech

10-EZ126PA035RA-L859F88T
datasheet

Packaging instruction				
Standard packaging quantity (SPQ) 100	>SPQ	Standard	<SPQ	Sample
Handling instruction				
Handling instructions for <i>flow</i> E1 packages see vincotech.com website.				
Package data				
Package data for <i>flow</i> E1 packages see vincotech.com website.				
Vincotech thermistor reference				
See Vincotech thermistor reference table at vincotech.com website.				
UL recognition and file number				
This device is UL 1557 recognized under E192116 up to a junction temperature under switching condition $T_{j,sp}=175^{\circ}\text{C}$ and up to 3500VAC/1min isolation voltage. For more information see vincotech.com website.				

Document No.:	Date:	Modification:	Pages
10-EZ126PA035RA-L859F88T-D1-14	15 Apr. 2025	Initial Release	

DISCLAIMER

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.