



Vincotech

# 10-E107L3A060ME-PM32L18Z

datasheet

flow3xNPFC 1

650 V / 60 mΩ

## Topology features

- 3xNeutral Boost PFC
- On-board Capacitors
- Temperature sensor

## Component features

- High Blocking Voltage with low drain source on state resistance
- High speed SiC-MOSFET technology
- Resistant to Latch-up

## Housing features

- Base isolation: Al<sub>2</sub>O<sub>3</sub>
- Convex shaped substrate for superior thermal contact
- Compact housing
- CTI600 housing material
- Thermo-mechanical push-and-pull force relief
- Solder pin


## Target applications

- Embedded Drives
- Heat Pumps
- HVAC
- Industrial Drives


## Types

- 10-E107L3A060ME-PM32L18Z

## flow E1 12 mm housing



## Schematic







Vincotech

**10-E107L3A060ME-PM32L18Z**  
datasheet

## Maximum Ratings

$T_j = 25\text{ °C}$ , unless otherwise specified

| Parameter | Symbol | Conditions | Value | Unit |
|-----------|--------|------------|-------|------|
|-----------|--------|------------|-------|------|

### Boost Switch

|                              |            |                                       |         |    |
|------------------------------|------------|---------------------------------------|---------|----|
| Drain-source voltage         | $V_{DS}$   |                                       | 650     | V  |
| Drain current (DC current)   | $I_D$      | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$ | 22      | A  |
| Peak drain current           | $I_{DM}$   | $t_p$ limited by $T_{jmax}$           | 99      | A  |
| Total power dissipation      | $P_{tot}$  | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$ | 47      | W  |
| Gate-source voltage          | $V_{GS}$   | static                                | -4 / 15 | V  |
|                              |            | dynamic                               | -8 / 19 | V  |
| Maximum Junction Temperature | $T_{jmax}$ |                                       | 175     | °C |

### Boost Diode

|  |            |  |      |    |
|--|------------|--|------|----|
| Peak repetitive reverse voltage        | $V_{RRM}$  |  | 1200 | V  |
| Forward current (DC current)           | $I_F$      | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$                                | 30   | A  |
| Repetitive peak forward current        | $I_{FRM}$  | $t_p$ limited by $T_{jmax}$  | 89   | A  |
| Surge (non-repetitive) forward current | $I_{FSM}$  | Single Half Sine Wave,<br>$t_p = 10\text{ ms}$ $T_j = 110\text{ °C}$ | 129  | A  |
| Total power dissipation                | $P_{tot}$  | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$                                | 63   | W  |
| Maximum junction temperature           | $T_{jmax}$ |  | 175  | °C |

### Capacitor (PFC)

|                       |           |  |             |    |
|-----------------------|-----------|--|-------------|----|
| Maximum DC voltage    | $V_{MAX}$ |  | 630         | V  |
| Operation Temperature | $T_{op}$  |  | -55 ... 150 | °C |





Vincotech

**10-E107L3A060ME-PM32L18Z**  
datasheet

## Maximum Ratings

$T_j = 25\text{ °C}$ , unless otherwise specified

| Parameter | Symbol | Conditions | Value | Unit |
|-----------|--------|------------|-------|------|
|-----------|--------|------------|-------|------|

## Module Properties

### Thermal Properties

|   |                  |  |                                  |    |
|---|------------------|--|----------------------------------|----|
| Storage temperature                             | $T_{\text{stg}}$ |  | -40...+125                       | °C |
| Operation temperature under switching condition | $T_{\text{jop}}$ |  | -40...+( $T_{\text{jmax}}$ - 25) | °C |

### Isolation Properties

|                            |                   |                                     |       |    |
|----------------------------|-------------------|-------------------------------------|-------|----|
| Isolation voltage          | $V_{\text{isol}}$ | DC Test Voltage* $t_p = 2\text{ s}$ | 6000  | V  |
| Creepage distance          |                   |                                     | >12,7 | mm |
| Clearance                  |                   |                                     | 9,1   | mm |
| Comparative Tracking Index | CTI               |                                     | ≥ 600 |    |

\*100 % tested in production





Vincotech

# 10-E107L3A060ME-PM32L18Z

datasheet

## Characteristic Values

| Parameter | Symbol | Conditions |                              |   |                                     |            | Values |     |     | Unit |
|-----------|--------|------------|------------------------------|---|-------------------------------------|------------|--------|-----|-----|------|
|           |        |            | $V_{GE}$ [V]<br>$V_{GS}$ [V] | $V_{CE}$ [V]<br>$V_{DS}$ [V]<br>$V_F$ [V] | $I_C$ [A]<br>$I_D$ [A]<br>$I_F$ [A] | $T_j$ [°C] | Min    | Typ | Max |      |

### Boost Switch

#### Static

|                                  |              |                     |       |     |       |                  |     |                    |                   |    |
|----------------------------------|--------------|---------------------|-------|-----|-------|------------------|-----|--------------------|-------------------|----|
| Drain-source on-state resistance | $r_{DS(on)}$ |                     | 15    |     | 13,2  | 25<br>125<br>150 | 42  | 77<br>84,3<br>87,3 | 79 <sup>(1)</sup> | mΩ |
| Gate-source threshold voltage    | $V_{GS(th)}$ |                     |       |     | 0,005 | 25               | 1,8 | 2,6                | 3,6               | V  |
| Gate to Source Leakage Current   | $I_{GSS}$    |                     | 15    | 0   |       | 25               |     | 10                 | 100               | nA |
| Zero Gate Voltage Drain Current  | $I_{DSS}$    |                     | 0     | 650 |       | 25               |     | 1                  | 50                | μA |
| Internal gate resistance         | $r_g$        |                     |       |     |       |                  |     | 3                  |                   | Ω  |
| Gate charge                      | $Q_g$        |                     | -4/15 | 400 | 13,2  | 25               |     | 46                 |                   | nC |
| Short-circuit input capacitance  | $C_{iss}$    | $f = 1 \text{ Mhz}$ | 0     | 600 | 0     | 25               |     | 1000               |                   | pF |
| Short-circuit output capacitance | $C_{oss}$    |                     |       |     |       |                  |     | 80                 |                   |    |
| Reverse transfer capacitance     | $C_{rss}$    |                     |       |     |       |                  |     | 9                  |                   |    |
| Diode forward voltage            | $V_{SD}$     |                     | 0     |     | 6,6   | 25               |     | 5,1                |                   | V  |

#### Thermal

|  |               |   |  |  |  |  |  |      |  |     |
|--|---------------|---|--|--|--|--|--|------|--|-----|
| Thermal resistance junction to sink <sup>(2)</sup> | $R_{th(j-s)}$ | $\lambda_{paste} = 5,2 \text{ W/mK}$<br>(PTM) |  |  |  |  |  | 2,04 |  | K/W |
|--|---------------|---|--|--|--|--|--|------|--|-----|

#### Dynamic

|                             |              |   |       |     |    |                  |  |                         |  |     |
|-----------------------------|--------------|---|-------|-----|----|------------------|--|-------------------------|--|-----|
| Turn-on delay time          | $t_{d(on)}$  | $R_{gon} = 8 \Omega$<br>$R_{goff} = 8 \Omega$ | -4/15 | 350 | 16 | 25<br>125<br>150 |  | 17,38<br>16,02<br>15,71 |  | ns  |
| Rise time                   | $t_r$        |   |       |     |    | 25<br>125<br>150 |  | 12,32<br>11,32<br>11,13 |  | ns  |
| Turn-off delay time         | $t_{d(off)}$ |   |       |     |    | 25<br>125<br>150 |  | 47,28<br>51,5<br>52,95  |  | ns  |
| Fall time                   | $t_f$        |   |       |     |    | 25<br>125<br>150 |  | 23,05<br>27,21<br>21,61 |  | ns  |
| Turn-on energy (per pulse)  | $E_{on}$     |   |       |     |    | 25<br>125<br>150 |  | 0,118<br>0,117<br>0,115 |  | mWs |
| Turn-off energy (per pulse) | $E_{off}$    |   |       |     |    | 25<br>125<br>150 |  | 0,022<br>0,026<br>0,026 |  | mWs |





Vincotech

# 10-E107L3A060ME-PM32L18Z

datasheet

## Characteristic Values

| Parameter | Symbol | Conditions |                              |   |                                     |            | Values |     |     | Unit |
|-----------|--------|------------|------------------------------|---|-------------------------------------|------------|--------|-----|-----|------|
|           |        |            | $V_{GE}$ [V]<br>$V_{GS}$ [V] | $V_{CE}$ [V]<br>$V_{DS}$ [V]<br>$V_F$ [V] | $I_C$ [A]<br>$I_D$ [A]<br>$I_F$ [A] | $T_j$ [°C] | Min    | Typ | Max |      |

### Boost Diode

#### Static

|                         |       |                |  |  |    |                  |  |                      |                  |    |
|-------------------------|-------|----------------|--|--|----|------------------|--|----------------------|------------------|----|
| Forward voltage         | $V_F$ |                |  |  | 20 | 25<br>125<br>150 |  | 1,33<br>1,54<br>1,62 | 2 <sup>(1)</sup> | V  |
| Reverse leakage current | $I_R$ | $V_r = 1200$ V |  |  |    | 25               |  | 5                    | 500              | µA |

#### Thermal

|  |               |                                       |  |  |  |  |  |      |  |     |
|--|---------------|---------------------------------------|--|--|--|--|--|------|--|-----|
| Thermal resistance junction to sink <sup>(2)</sup> | $R_{th(j-s)}$ | $\lambda_{paste} = 5,2$ W/mK<br>(PTM) |  |  |  |  |  | 1,51 |  | K/W |
|--|---------------|---------------------------------------|--|--|--|--|--|------|--|-----|

#### Dynamic

|                                       |                      |   |       |     |    |                  |  |                               |  |      |
|---------------------------------------|----------------------|---|-------|-----|----|------------------|--|-------------------------------|--|------|
| Peak recovery current                 | $I_{RM}$             | $di/dt=1482$ A/µs<br>$di/dt=1577$ A/µs<br>$di/dt=1609$ A/µs | -4/15 | 350 | 16 | 25<br>125<br>150 |  | 12,69<br>13,59<br>13,92       |  | A    |
| Reverse recovery time                 | $t_{rr}$             |   |       |     |    | 25<br>125<br>150 |  | 21,5<br>20,38<br>20,1         |  | ns   |
| Recovered charge                      | $Q_r$                |   |       |     |    | 25<br>125<br>150 |  | 0,157<br>0,165<br>0,167       |  | µC   |
| Reverse recovered energy              | $E_{rec}$            |   |       |     |    | 25<br>125<br>150 |  | 0,025<br>0,028<br>0,028       |  | mWs  |
| Peak rate of fall of recovery current | $(di_{rr}/dt)_{max}$ |   |       |     |    | 25<br>125<br>150 |  | 1057,62<br>1074,77<br>1165,22 |  | A/µs |





Vincotech

**10-E107L3A060ME-PM32L18Z**  
datasheet

**Characteristic Values**

| Parameter | Symbol | Conditions |                              |   |                                     |            | Values |     |     | Unit |
|-----------|--------|------------|------------------------------|---|-------------------------------------|------------|--------|-----|-----|------|
|           |        |            | $V_{GE}$ [V]<br>$V_{GS}$ [V] | $V_{CE}$ [V]<br>$V_{DS}$ [V]<br>$V_F$ [V] | $I_C$ [A]<br>$I_D$ [A]<br>$I_F$ [A] | $T_j$ [°C] | Min    | Typ | Max |      |

**Capacitor (PFC)**

**Static**

|             |     |                       |  |  |  |    |    |    |   |    |
|-------------|-----|-----------------------|--|--|--|----|----|----|---|----|
| Capacitance | $C$ | DC bias voltage = 0 V |  |  |  | 25 |    | 33 |   | nF |
| Tolerance   |     |                       |  |  |  |    | -5 |    | 5 | %  |

**Thermistor**

**Static**

|                                |                |                        |  |  |  |     |     |      |     |      |
|--------------------------------|----------------|------------------------|--|--|--|-----|-----|------|-----|------|
| Rated resistance               | $R$            |                        |  |  |  | 25  |     | 5    |     | kΩ   |
| Deviation of R100              | $\Delta_{R/R}$ | $R_{100} = 499 \Omega$ |  |  |  | 100 | 3,2 |      | 3,3 | %    |
| Power dissipation              | $P$            |                        |  |  |  | 25  |     | 130  |     | mW   |
| Power dissipation constant     | $d$            |                        |  |  |  | 25  |     | 1,3  |     | mW/K |
| B-value                        | $B_{(25/50)}$  | Tol. $\pm 1 \%$        |  |  |  |     |     | 3380 |     | K    |
| Vincotech Thermistor Reference |                |                        |  |  |  |     |     |      | V   |      |

<sup>(1)</sup> Value at chip level

<sup>(2)</sup> Only valid with pre-applied Vincotech thermal interface material.






Vincotech

## Boost Switch Characteristics

figure 1. MOSFET

Typical output characteristics

$$I_D = f(V_{DS})$$




$t_p = 250 \mu s$   
 $V_{GS} = 15 V$

$T_j$ :  
— 25 °C  
— 125 °C  
— 150 °C

figure 2. MOSFET

Typical output characteristics

$$I_D = f(V_{DS})$$




$t_p = 250 \mu s$   
 $T_j = 150 ^\circ C$   
 $V_{GS}$  from -4 V to 15 V in steps of 2 V

figure 3. MOSFET

Typical transfer characteristics

$$I_D = f(V_{GS})$$




$t_p = 250 \mu s$   
 $V_{DS} = 10 V$

$T_j$ :  
— 25 °C  
— 125 °C  
— 150 °C

figure 4. MOSFET

Typical reverse drain current characteristics

$$I_{SD} = f(V_{SD})$$



$t_p = 250 \mu s$   
 $V_{GS} = 15 V$

$T_j$ :  
— 25 °C  
— 125 °C  
— 150 °C






Vincotech

## Boost Switch Characteristics

figure 5. MOSFET

Transient thermal impedance as a function of pulse width

$$Z_{th(j-a)} = f(t_p)$$



$$D = t_p / T$$

$$R_{th(j-a)} = 2,036 \text{ K/W}$$


MOSFET thermal model values

| R (K/W)  | $\tau$ (s) |
|----------|------------|
| 1,74E-02 | 8,78E+00   |
| 1,01E-01 | 1,50E+00   |
| 6,98E-01 | 9,13E-02   |
| 8,28E-01 | 1,78E-02   |
| 3,92E-01 | 1,37E-03   |

figure 7. MOSFET

Gate voltage vs gate charge

$$V_{GS} = f(Q_g)$$




$$I_D = 13.2 \text{ A}$$
$$T_j = 25 \text{ }^{\circ}\text{C}$$

figure 6. MOSFET

Safe operating area

$$I_D = f(V_{DS})$$



D = single pulse

$$T_s = 80 \text{ }^{\circ}\text{C}$$

$$V_{GS} = 15 \text{ V}$$

$$T_j = T_{jmax}$$





Boost Diode Characteristics

figure 8. FWD

Typical forward characteristics  
 $I_F = f(V_F)$





figure 9. FWD

Transient thermal impedance as a function of pulse width  
 $Z_{th(j-s)} = f(t_p)$







Vincotech

**10-E107L3A060ME-PM32L18Z**  
datasheet


## Thermistor Characteristics

figure 10.

Thermistor

Typical NTC characteristic as function of temperature

$$R_T = f(T)$$







Vincotech

10-E107L3A060ME-PM32L18Z  
datasheet


## Boost Switching Characteristics

figure 11.

MOSFET

Typical switching energy losses as a function of drain current

$$E = f(I_D)$$



With an inductive load at

$V_{DS} = 350$  V  
 $V_{GS} = -4/15$  V  
 $R_{gon} = 8$   $\Omega$   
 $R_{goff} = 8$   $\Omega$


$T_j$ : 25 °C  
125 °C  
150 °C

figure 12.

MOSFET

Typical switching energy losses as a function of MOSFET turn on gate resistor

$$E = f(R_g)$$



With an inductive load at

$V_{DS} = 350$  V  
 $V_{GS} = -4/15$  V  
 $I_D = 16$  A


$T_j$ : 25 °C  
125 °C  
150 °C

figure 13.

FWD

Typical reverse recovered energy loss as a function of drain current

$$E_{rec} = f(I_D)$$



With an inductive load at

$V_{DS} = 350$  V  
 $V_{GS} = -4/15$  V  
 $R_{gon} = 8$   $\Omega$


$T_j$ : 25 °C  
125 °C  
150 °C

figure 14.

FWD

Typical reverse recovered energy loss as a function of MOSFET turn on gate resistor

$$E_{rec} = f(R_g)$$



With an inductive load at

$V_{DS} = 350$  V  
 $V_{GS} = -4/15$  V  
 $I_D = 16$  A

$T_j$ : 25 °C  
125 °C  
150 °C






Vincotech

# 10-E107L3A060ME-PM32L18Z datasheet

## Boost Switching Characteristics

figure 15. MOSFET

Typical switching times as a function of drain current  
 $t = f(I_D)$




With an inductive load at

$T_j = 150$  °C  
 $V_{DS} = 350$  V  
 $V_{GS} = -4/15$  V  
 $R_{gon} = 8$  Ω  
 $R_{goff} = 8$  Ω

figure 16. MOSFET

Typical switching times as a function of MOSFET turn on gate resistor  
 $t = f(R_g)$




With an inductive load at

$T_j = 150$  °C  
 $V_{DS} = 350$  V  
 $V_{GS} = -4/15$  V  
 $I_D = 16$  A

figure 17. FWD


Typical reverse recovery time as a function of drain current  
 $t_{rr} = f(I_D)$



At  $V_{DS} = 350$  V  
 $V_{GS} = -4/15$  V  
 $R_{gon} = 8$  Ω  
 $T_j: 25$  °C (blue)  
 $125$  °C (black)  
 $150$  °C (red)

figure 18. FWD

Typical reverse recovery time as a function of MOSFET turn on gate resistor  
 $t_{rr} = f(R_{gon})$



At  $V_{DS} = 350$  V  
 $V_{GS} = -4/15$  V  
 $I_D = 16$  A  
 $T_j: 25$  °C (blue)  
 $125$  °C (black)  
 $150$  °C (red)





Vincotech

10-E107L3A060ME-PM32L18Z  
datasheet


## Boost Switching Characteristics

figure 19.

FWD

Typical recovered charge as a function of drain current

$$Q_r = f(I_D)$$




At  $V_{DS} = 350$  V  
 $V_{GS} = -4/15$  V  
 $R_{gon} = 8$  Ω  
 $T_j$ : 25 °C (blue), 125 °C (black), 150 °C (red)

figure 20.

FWD

Typical recovered charge as a function of MOSFET turn on gate resistor

$$Q_r = f(R_{gon})$$




At  $V_{DS} = 350$  V  
 $V_{GS} = -4/15$  V  
 $I_D = 16$  A  
 $T_j$ : 25 °C (blue), 125 °C (black), 150 °C (red)

figure 21.

FWD

Typical peak reverse recovery current as a function of drain current

$$I_{RM} = f(I_D)$$




At  $V_{DS} = 350$  V  
 $V_{GS} = -4/15$  V  
 $R_{gon} = 8$  Ω  
 $T_j$ : 25 °C (blue), 125 °C (black), 150 °C (red)

figure 22.

FWD

Typical peak reverse recovery current as a function of MOSFET turn on gate resistor

$$I_{RM} = f(R_{gon})$$



At  $V_{DS} = 350$  V  
 $V_{GS} = -4/15$  V  
 $I_D = 16$  A  
 $T_j$ : 25 °C (blue), 125 °C (black), 150 °C (red)






Vincotech

# 10-E107L3A060ME-PM32L18Z datasheet

## Boost Switching Characteristics

figure 23. FWD


Typical rate of fall of forward and reverse recovery current as a function of drain current  
 $di_f/dt, di_r/dt = f(I_D)$



At  $V_{DS} = 350$  V  
 $V_{GS} = -4/15$  V  
 $R_{gon} = 8$   $\Omega$   
 $T_j = 25$  °C  
 $125$  °C  
 $150$  °C

figure 24. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn on gate resistor  
 $di_f/dt, di_r/dt = f(R_{gon})$




At  $V_{DS} = 350$  V  
 $V_{GS} = -4/15$  V  
 $I_D = 16$  A  
 $T_j = 25$  °C  
 $125$  °C  
 $150$  °C

figure 25. MOSFET

Reverse bias safe operating area

$I_D = f(V_{DS})$



At  $T_j = 150$  °C  
 $R_{gon} = 8$   $\Omega$   
 $R_{goff} = 8$   $\Omega$





Vincotech

## Boost Switching Definitions

figure 26. MOSFET

Turn-off Switching Waveforms & definition of  $t_{doff}$   $t_{Eoff}$  ( $t_{Eoff}$  = integrating time for  $E_{off}$ )




figure 27. MOSFET

Turn-on Switching Waveforms & definition of  $t_{don}$   $t_{Eon}$  ( $t_{Eon}$  = integrating time for  $E_{on}$ )




figure 28. MOSFET

Turn-off Switching Waveforms & definition of  $t_f$





figure 29. MOSFET

Turn-on Switching Waveforms & definition of  $t_r$







Vincotech

## Boost Switching Definitions

figure 30.

FWD

Turn-off Switching Waveforms & definition of  $t_{rr}$




figure 31.

FWD

Turn-on Switching Waveforms & definition of  $t_{Qr}$  ( $t_{Qr}$  = integrating time for  $Q_r$ )





figure 32.

FWD

Turn-on Switching Waveforms & definition of  $t_{Erec}$  ( $t_{Erec}$  = integrating time for  $E_{rec}$ )







Vincotech

10-E107L3A060ME-PM32L18Z  
datasheet

| Ordering Code                            |                              |
|--|------------------------------|
| Version                                  | Ordering Code                |
| Without thermal paste                    | 10-E107L3A060ME-PM32L18Z     |
| With thermal paste (5,2 W/mK, PTM6000HV) | 10-E107L3A060ME-PM32L18Z-/7/ |


| Marking |            |                               |            |          |           |        |
|---------|------------|-------------------------------|------------|----------|-----------|--------|
|         | Text       | Name                          | Date code  | UL & VIN | Lot       | Serial |
|         |            | NN-NNNNNNNNNNNNNNNN- TTTTWWYY | WWYY       | UL VIN   | LLLL      | SSSS   |
|         | Datamatrix | Type&Ver                      | Lot number | Serial   | Date code |        |
|         |            | TTTTTTVV                      | LLLLL      | SSSS     | WWYY      |        |

| Pin table [mm] |      |      |          |
|----------------|------|------|----------|
| Pin            | X    | Y    | Function |
| 1              | 0    | 12,8 | ACIn1    |
| 2              | 12,8 | 12,8 | ACIn2    |
| 3              | 22,4 | 12,8 | ACIn3    |
| 4              | 0    | 25,6 | DC-1     |
| 5              | 3,2  | 19,2 | GND1     |
| 6              | 9,6  | 25,6 | DC+12    |
| 7              | 16   | 25,6 | GND2     |
| 8              | 22,4 | 25,6 | DC-23    |
| 9              | 25,6 | 19,2 | GND3     |
| 10             | 32   | 25,6 | DC+3     |
| 11             | 3,2  | 0    | G1       |
| 12             | 6,4  | 0    | S1       |
| 13             | 16   | 0    | G2       |
| 14             | 19,2 | 0    | S2       |
| 15             | 28,8 | 0    | G3       |
| 16             | 32   | 0    | S3       |
| 17             | 32   | 12,8 | Therm1   |
| 18             | 32   | 16   | Therm2   |





Vincotech




| Identification               |            |         |         |                 |         |
|------------------------------|------------|---------|---------|-----------------|---------|
| ID                           | Component  | Voltage | Current | Function        | Comment |
| C11, C12, C13, C14, C15, C16 | Capacitor  | 630 V   |         | Capacitor (PFC) |         |
| T13, T14, T23, T24, T33, T34 | MOSFET     | 650 V   | 60 mΩ   | Boost Switch    |         |
| D13, D14, D23, D24, D33, D34 | FWD        | 1200 V  | 20 A    | Boost Diode     |         |
| Rt                           | Thermistor |         |         | Thermistor      |         |





Vincotech

**10-E107L3A060ME-PM32L18Z**  
datasheet

| Packaging instruction   |      |          |      |   |
|---|------|----------|------|---|
| Standard packaging quantity (SPQ) 100   | >SPQ | Standard | <SPQ | Sample  |
| Handling instruction  |      |          |      |   |
| Handling instructions for <i>flow</i> E1 packages see vincotech.com website.  |      |          |      |   |
| Package data  |      |          |      |   |
| Package data for <i>flow</i> E1 packages see vincotech.com website.   |      |          |      |   |
| Vincotech thermistor reference  |      |          |      |   |
| See Vincotech thermistor reference table at vincotech.com website.  |      |          |      |   |
| UL recognition and file number  |      |          |      |   |
| This device is UL 1557 recognized under E192116 up to a junction temperature under switching condition $T_{j,sp}=175^{\circ}\text{C}$ and up to 3500VAC/1min isolation voltage. For more information see vincotech.com website. |      |          |      |  |

| Document No.:                  | Date:        | Modification:  | Pages |
|--------------------------------|--------------|----------------|-------|
| 10-E107L3A060ME-PM32L18Z-D2-14 | 21 May. 2025 | Change Housing |       |

**DISCLAIMER**

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

**LIFE SUPPORT POLICY**

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.